
## RESIDENTIAL TRUE OAK® DEEP CORRUGATE WALL CLADDING METER BOX SIDE FLASHING FOR HORIZONTAL CLADDING

Detail No. RI-RTDW04 | A Date drawn: 01/02/2020


Scale: 1:5@ A4

Version: 01



## NOTES:

- I. CAVITY BATTENS CONTAINING CORROSIVE
  MATERIAL MUST BE SEPARATED FROM METAL
  CLADDING BY DPC, BUILDING WRAP, PVC OR
  PAINTING.
- REFER TO E2/AS I FOR GENERAL METERBOX AND SIMILAR PENETRATIONS / OPENINGS.



\*Back tray size may require to increase to ensure coverage at ends of head flashing. (Dimensions are indicative only) Turn down end of head flashing

 These details are generally in compliance with E2/AS I and/or the NZ Metal Roof \$ Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'.

NOTES:

- The building designer is ultimately responsible to ensure that details used meet the requirements of the NZ Building Code for the specific project.
- Details of the supporting structure including cavity battens are indicative only and are the responsibility of the building designer. For steel framed buildings thermal break cavity battens may be required.
- Underlay selection and building wrap types are the responsibility of the designer. When rigid wall underlay is
  required it is the designers responsibility to ensure the correct type is used and follow the manufacturers
  recommendation for installation.
- These details are for Roofing Industries profile/s as nominated and may not be applicable to other profiles.
- This drawing is the copyright of 'Roofing Industries' and can only be copied or reproduced with their permission.
- Further information can be obtained from the NZ Metal Roof \$ Wall Cladding Code of Practice: www.metalroofing.org.nz or E2/ASI.

Copyright detail © 2020

