


**Product Details**

range name	GB VENEER
finish	SPLIT FACE
colours	PORCELAIN   NICKEL   PEWTER   LIMESTONE   PEBBLE
product code   description	10.117   90MM SPLIT FACE 40MM VENEER

**Properties and Specifications**

nominal dimensions (length x width x height mm)	100 x 50 x 400mm
actual dimensions (length x width x height mm)	90 x 40 x 390mm
core volume (% overall thickness)	-
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	-
average weight (KG)	3.1
units per tonne	323
number per pallet	480
number per sqm/lm	50 OR 2.5 PER LM
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	150
wall mass inc grouted solid	-
Light Reflectance Value	-

**Diagram**



**Fire Resistance Levels<sup>^</sup>**

structural adequacy (see notes)	60 to 240
integrity	60
insulation	60

**Notes**

Maximum slenderness ratio (srf) unreinforced masonry from AS3700:2018 Table 6.1 is:

18.0 at 60 minutes | 17.0 at 90 minutes

16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes

*This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999.*

<sup>^</sup>When reinforced and Srf <36: 240 minutes




**Product Details**

range name	GB VENEER
finish	SAWN FACE
colours	PORCELAIN   NICKEL   PEWTER   LIMESTONE   PEBBLE
product code   description	10.117   90MM SAWN FACE 40MM VENEER

**Properties and Specifications**

nominal dimensions (length x width x height mm)	100 x 50 x 400mm
actual dimensions (length x width x height mm)	90 x 40 x 390mm
core volume (% overall thickness)	-
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	-
average weight (KG)	3.1
units per tonne	323
number per pallet	480
number per sqm/lm	50 OR 2.5 PER LM
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	150
wall mass inc grouted solid	-
Light Reflectance Value	-

**Diagram**



**Fire Resistance Levels<sup>^</sup>**

structural adequacy (see notes)	60 to 240
integrity	60
insulation	60

**Notes**

Maximum slenderness ratio (srf) unreinforced masonry from AS3700:2018 Table 6.1 is:

18.0 at 60 minutes | 17.0 at 90 minutes

16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes

*This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999.*

<sup>^</sup>When reinforced and Srf <36: 240 minutes