




DE NIRO

NEW-BUILD 90MM LED DOWNLIGHT



- The De Niro range of LED downlights share a uniform bulb and driver set, which twist and click into the different fascia styles.
- Gimbal adjustment feature to suit angled ceilings, and directional lighting applications – 25° Tilt
- IC-4 Rated, can be abutted and covered with approved insulation materials




| Code | Type | Power (W) | Lumens Output | Colour Temp (k) | Fascia (mm) | Cutout (mm) | Glare |
|------|--------|-----------|---------------|-----------------|-------------|-------------|--------|
| NC3 | White | 8 | 700 | 3000 | 90 Ø | 70-80 | UGR<22 |
| NC4 | White | 8 | 730 | 4000 | 90 Ø | 70-80 | UGR<22 |
| NC3S | Silver | 8 | 700 | 3000 | 90 Ø | 70-80 | UGR<22 |
| NC4S | Sliver | 8 | 730 | 4000 | 90 Ø | 70-80 | UGR<22 |
| NC3B | Black | 8 | 700 | 3000 | 90 Ø | 70-80 | UGR<22 |
| NC4B | Black | 8 | 730 | 4000 | 90 Ø | 70-80 | UGR<22 |

High Output units can be made available on request
Made to order locally, short delays may occur



DE NIRO

RETROFIT 110MM LED DOWNLIGHT



- The De Niro range of LED downlights share a uniform bulb and driver set, which twist and click into the different fascia styles.
- Gimbal adjustment feature to suit angled ceilings, and directional lighting applications – 25° Tilt
- IC-4 Rated, can be abutted and covered with approved insulation materials



| Code | Type | Power (W) | Lumens Output | Colour Temp (k) | Fascia (mm) | Cutout (mm) | Glare |
|-------|--------------|-----------|---------------|-----------------|-------------|-------------|--------|
| NR3 | Retro White | 8 | 700 | 3000 | 110 Ø | 70-92 | UGR<22 |
| NR4 | Retro White | 8 | 730 | 4000 | 110 Ø | 70-92 | UGR<22 |
| NR3S* | Retro Silver | 8 | 700 | 3000 | 110 Ø | 70-92 | UGR<22 |
| NR4S* | Retro Silver | 8 | 730 | 4000 | 110 Ø | 70-92 | UGR<22 |
| NR3B* | Retro Black | 8 | 700 | 3000 | 110 Ø | 70-92 | UGR<22 |
| NR4B* | Retro Black | 8 | 730 | 4000 | 110 Ø | 70-92 | UGR<22 |

High Output units can be made available on request
Made to order locally, short delays may occur

*Black and Silver available on request MOQs apply

IP40
PROTECTION RATING

DIMMABLE

90
COLOUR RENDERING


60°
BEAM ANGLE

5
YEAR
WARRANTY



DE NIRO

SQUARE LED DOWNLIGHT



- The De Niro range of LED downlights share a uniform bulb and driver set, which twist and click into the different fascia styles.
- Gimbal adjustment feature to suit angled ceilings, and directional lighting applications – 25° Tilt
- IC-4 Rated, can be abutted and covered with approved insulation materials



| Code | Type | Power (W) | Lumens Output | Colour Temp (k) | Fascia (mm) | Cutout (mm) | Glare |
|--------|---------------|-----------|---------------|-----------------|-------------|-------------|--------|
| NSQ3 | Square White | 8 | 700 | 3000 | 110 SQ | 70-92 | UGR<22 |
| NSQ4 | Square White | 8 | 730 | 4000 | 110 SQ | 70-92 | UGR<22 |
| NSQ3S* | Square Silver | 8 | 700 | 3000 | 110 SQ | 70-92 | UGR<22 |
| NSQ4S* | Square Silver | 8 | 730 | 4000 | 110 SQ | 70-92 | UGR<22 |
| NSQ3B* | Square Black | 8 | 700 | 3000 | 110 SQ | 70-92 | UGR<22 |
| NSQ4B* | Square Black | 8 | 730 | 4000 | 110 SQ | 70-92 | UGR<22 |

High Output units can be made available on request
Made to order locally, short delays may occur

*Black and Silver available on request MOQs apply