

Fast assembly concealed hinge with integrated Silent System







- ▶ Sensys 8631i for thick doors
- ▶ 95° opening angle



- ▶ Concealed clip on hinge with Integrated Silent System
- ▶ Quality classification in accordance with EN 15570, Level 2
- ▶ For door thickness of 15 – 32 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated overlay adjustment + 2 mm / - 2 mm
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Hinge arm material: nickel plated steel
- ▶ Hinge cup material: nickel plated steel

Sensys 8631i, 95° opening angle

Cup Installation	Drilling pattern	Fixing hole ø x T mm	Full overlay	Half overlay	Inset	PU
						
Screw on version TH 52		-	Basis B 12.5 mm	Basis B 3 mm	Basis B - 4 mm	200 ea.
Press in version TH 53		ø 10 x 11	9 090 260	9 090 270	9 090 280	200 ea.
Flash fast assembly TH 54		ø 10 x 11	9 090 261	9 090 271	9 090 281	200 ea.
			9 090 262	9 090 272	9 090 282	200 ea.

Fast assembly concealed hinge

- ▶ Sensys 8631i for thick doors
- ▶ 95° opening angle



Minimum reveal per door

Door thickness mm	Cup distance C mm							
	2.0	4.0	4.5	5.0	6.0	7.0	8.0	8.0
15	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
16	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
17	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
18	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
19	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
20	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
21	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
22	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7
23	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9
24	1.1	1.0	1.0	1.0	1.0	1.0	1.0	1.0
25	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
26	1.5	1.5	1.4	1.4	1.4	1.4	1.4	1.4
27	1.7	1.7	1.7	1.7	1.6	1.6	1.6	1.6
28	2.0	2.0	1.9	1.9	1.9	1.8	1.8	1.8
29	2.9	2.3	2.2	2.2	2.2	2.1	2.1	2.1
30	3.8	3.2	3.0	2.7	2.5	2.4	2.4	2.4
31	4.8	4.1	3.8	3.5	3.1	2.7	2.7	2.7
32	5.7	5.1	4.8	4.5	3.9	3.4	3.0	3.0

Note:


The values in the table refer to doors with an edge radius of 1 mm.

On doors with other radii, the minimum reveal changes as follows:

Radius 0 mm:

Value in table + 0.4 mm


Installation dimensions



Hinge protrusion H / door protrusion T for distance D = 0 mm and cup distance C = 3 mm

Door mounting option	H mm	T mm
Full overlay	24.0	12.5
Half overlay	28.3	22.0
Inset	35.3	29.0


Full overlay



Distance D = C + B - A
= cup distance C + 12.5 mm - overlay A

Overlay mm	Cup distance C mm							
	2.0	4.0	4.5	5.0	6.0	7.0	8.0	8.0
10	6.5	6.5	7.0	7.5	8.5	9.5	10.5	
11	4.5	5.5	6.0	6.5	7.5	8.5	9.5	
12	3.5	4.5	5.0	5.5	6.5	7.5	8.5	
13	2.5	3.5	4.0	4.5	5.5	6.5	7.5	
14	1.5	2.5	3.0	3.5	4.5	5.5	6.5	
15	0.5	1.5	2.0	2.5	3.5	4.5	5.5	
16		0.5	1.0	1.5	2.5	3.5	4.5	
17			0.0	0.5	1.5	2.5	3.5	
18					0.5	1.5	2.5	
19						0.5	1.5	
20							0.5	

Half overlay



Distance D = C + B - A
= cup distance C + 3 mm - overlay A

Overlay mm	Cup distance C mm							
	2.0	4.0	4.5	5.0	6.0	7.0	8.0	8.0
0.5	6.5	6.5	7.0	7.5	8.5	9.5	10.5	
1.5	4.5	5.5	6.0	6.5	7.5	8.5	9.5	
2.5	3.5	4.5	5.0	5.5	6.5	7.5	8.5	
3.5	2.5	3.5	4.0	4.5	5.5	6.5	7.5	
4.5	1.5	2.5	3.0	3.5	4.5	5.5	6.5	
5.5	0.5	1.5	2.0	2.5	3.5	4.5	5.5	
6.5		0.5	1.0	1.5	2.5	3.5	4.5	
7.5			0.0	0.5	1.5	2.5	3.5	
8.5					0.5	1.5	2.5	
9.5						0.5	1.5	
10.5							0.5	

Inset



Distance D = C + B + F
= cup distance C - 4 mm + reveal F

Door thickness mm	Cup distance C mm							
	2.0	4.0	4.5	5.0	6.0	7.0	8.0	8.0
15	0.1	0.6	1.1	2.1	3.1	3.1	4.1	
16	0.1	0.6	1.1	2.1	3.1	3.1	4.1	
17	0.2	0.7	1.2	2.2	3.2	3.2	4.2	
18	0.2	0.7	1.2	2.2	3.2	3.2	4.2	
19	0.3	0.8	1.3	2.3	3.3	3.3	4.3	
20	0.4	0.9	1.4	2.4	3.4	3.4	4.4	
21	0.6	1.1	1.6	2.6	3.6	3.6	4.6	
22	0.7	1.2	1.7	2.7	3.7	3.7	4.7	
23	0.9	1.4	1.9	2.9	3.9	3.9	4.9	
24	0.1	1.0	1.5	2.0	3.0	4.0	5.0	
25	0.3	1.2	1.7	2.2	3.2	4.2	5.2	
26	0.5	1.5	1.9	2.4	3.4	4.4	5.4	
27	0.7	1.7	2.2	2.7	3.6	4.6	5.6	
28	1.0	2.0	2.4	2.9	3.8	4.8	5.8	
29	1.9	2.3	2.7	3.2	4.2	5.1	6.1	
30	2.8	3.2	3.5	3.7	4.5	5.4	6.4	
31	3.8	4.1	4.3	4.6	5.1	5.7	6.7	
32	4.7	5.1	5.3	5.6	5.9	6.4	7.0	

▶ Advice

For mounting plates, see pages 28 - 29

For accessories, see pages 30 - 31

For technical information, see pages 32 - 39

For example applications, see page 32 - 33

Fast assembly concealed hinge


- ▶ Sensys 8631i for thick doors
- ▶ Opening angle 95°

Door contours for minimum reveal application - scale 1:1

The values shown in the Minimum reveal table refer to an edge radius of 1 mm.
Smaller reveal values apply if door edges are more rounded.
To obtain a minimum reveal application, the chosen door contour must lie within the template illustrated below. All contours protruding beyond the template will increase the reveal accordingly.




Examples of minimum reveal application



Example of minimum reveal application

Door thickness	16 mm
Profile thickness	12 mm
Overall thickness	28 mm
Cup distance C	4 mm



Example of minimum reveal application

Door thickness	19 mm
Profile thickness	13 mm
Overall thickness	32 mm
Cup distance C	8 mm