

## Fast assembly concealed hinge with integrated Silent System







- ▶ Sensys 8645i
- ▶ 110° opening angle



- ▶ Concealed clip on hinge with Integrated Silent System
- ▶ Quality classification in accordance with EN 15570, Level 3
- ▶ For door thickness of 15 - 24 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated overlay adjustment + 2 mm / - 2 mm
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment of mounting plate
- ▶ Hinge arm material: nickel plated steel
- ▶ Hinge cup material: nickel plated steel

Sensys 8645i, 110° opening angle

Cup Installation	Drilling pattern	Fixing hole ø x T mm	Full overlay	Half overlay	Inset	PU
						
Screw on version TH 52		-	Basis B 12.5 mm	Basis B 3 mm	Basis B - 4 mm	200 ea.
Press in version TH 53		ø 10 x 11	9 071 205	9 071 206	9 071 207	200 ea.
Flash fast assembly TH 54		ø 10 x 11	9 071 208	9 071 209	9 071 210	200 ea.
Fix fast assembly THS 55		ø 10 x 6	9 071 211	9 071 212	9 071 213	200 ea.
			9 071 220	9 071 221	9 071 222	200 ea.