




Timber Construction

NEW SPAX 6mm and 8mm countersunk universal screw in A2/304 Stainless Steel

T-STAR *plus*



MULTI Head



4CUT cutter



Ground Serration
4CUT point




Ideal to use on any outdoor timber structure
including replacing failed batten screws.



- For timber structures where flush countersinking is necessary
- Higher load capacities than traditional screws
- Quick and easy installation with low installation torque saving tool and battery life
- 8mm also available in **DELTA® - SEAL**

SPAX Countersunk Universal Screw

Stainless Steel A2/304



Dimensions [mm]				Packaging unit	SPAX-No.	EAN-Code
Thread Ø d1	Length total Ls	Length partial thread LgT	BIT size T	SPAX BOX [pieces]		
6.0 Ø d _k = 11.6mm	60	37	30	100	0197000600603	4003530091988
	70	41	30	100	0197000600703	4003530091995
	80	46	30	100	0197000600803	4003530092008
	90	61	30	100	0197000600903	4003530092015
	100	61	30	100	0197000601003	4003530092022
	120	68	30	100	0197000601203	4003530097775
	140	68	30	100	0197000601403	4003530097782
	160	65	30	100	0197000601603	4003530098727
8.0 Ø d _k = 15.1mm	80	47	40	50	0197000800805	4003530257292
	100	57	40	50	0197000801005	4003530257308
	120	70	40	50	0197000801205	4003530257315
	140	80	40	50	0197000801405	4003530257322
	160	80	40	50	0197000801605	4003530257339
	180	80	40	50	0197000801805	4003530257346
	200	80	40	50	0197000802005	4003530257353
	220	80	40	50	0197000802205	4003530257360
	240	80	40	50	0197000802405	4003530257377
	260	80	40	50	0197000802605	4003530257384
	280	80	40	50	0197000802805	4003530257391
	300	80	40	50	0197000803005	4003530257407

