



The range

Ambience is European Poplar plywood with different wood grain finishes: Poplar, Birch, Eucalypt and Okoume. These panels are available both unfinished and pre-finished, ready to be installed without the hassle of additional finishing.

Ambience - Poplar

Manufactured from selected high quality Italian Poplar veneer which has been "blonded" to achieve a consistent creamy-white appearance. Ambience — Poplar is creamy-white in colour. Straight grained with a fine and even, woolly texture.

Ambience - Birch

Stable and lightweight European manufactured Poplar plywood with a decorative Birch veneer face and back. Ambience – Birch is creamy-white to biscuit in colour with a straight grain and fine texture.

Ambience - Eucalypt

Stable and lightweight European manufactured Poplar plywood with a decorative Eucalypt veneer face and back. Ambience – Eucalypt is light in colour, ranging from straw to reddish brown. Predominantly straight grained.

Ambience - Okoume

Stable and lightweight European manufactured Poplar plywood with a decorative Okoume veneer face and back. Ambience – Okoume is light in colour, ranging from straw to brown. Straight to slightly wavy grain and an even medium texture.



Technical information

Ambience – Poplar				
SIZE	THICKNESS	KG	FINISH	
2500 x 1220	10mm	13kg	Uncoated	
2500 x 1220	12mm	15.3kg	Uncoated	
2500 x 1220	18mm	21.5kg	Uncoated	
2440 x 1220	12mm	15.3kg	Coated (<i>PF</i>)	

Ambience – Birch					
Size	Thickness	KG	Finish		
2440 x 1220	10mm	13kg	Uncoated		
2440 x 1220	12mm	15.3kg	Uncoated		
2440 x 1220	12mm	15.3kg	Coated (PF)		

Ambience – Eucalypt					
SIZE	THICKNESS	KG	FINISH		
2500 x 1220	12mm	15.3kg	Uncoated		
2500 x 1220	12mm	15.3kg	Coated (PF)		

Ambience – Okoume					
SIZE	THICKNESS	KG	FINISH		
2500 x 1220	12mm	15.3kg	Uncoated		
2500 x 1220	12mm	15.3kg	Coated (PF)		

Easy installation:

This lightweight panel (12mm)weighing only 16kg (two-thirds the weight of 13mm plasterboard) can be easily handled and installed by one person.

Pre- finished:

The Ambience range is also available prefinished ready to be installed without the hassle of additional finishing.

Technical Specifications:

Standard – EN 635 Wood Raw Material – Black Italian Poplar Density – average 420kg/m3 Class – Hardwood, non-durable Glue Bond – EN 314-1: Class 1 Interior Glue Formaldehyde Emissions – ULEF: Ultra Low Emitting Formaldehyde.

Environment:

Environment Protection Standard: ISO 14001:2004 Quality Management Standard: ISO 9001:2008 ULEF: No harmful emissions FSC Certified PEFC Certified.

Handling and Storage:

Plywood is a natural product that can be affected by changes in ambient weather conditions, causing previously flat sheets to bow or twist. All precautions are taken to minimise this effect, however once the plywood has left our warehouse we cannot guarantee sheets to remain flat. This is particularly important where free

