

Formaldehyde Emission Classifications

The Engineered Wood Products Association of Australasia Ltd. certifies that

Austral Plywoods Pty Ltd 1 Curzon Street, Tennyson Qld 4105 Mill Number **411**

manufactures the following products which continue to satisfy the EWPAA Plywood and LVL Scheme Rules for Certification with regard to formaldehyde emission. This is based on a rolling three monthly average of NATA accredited laboratory test results complying with the limits specified in the relevant standard^{*}. Testing is conducted in accordance with AS/NZS 2098.11: 2005

| Product | Standard Certified Against | Bond Type | Emission |
|---------|---|-----------|----------|
| Plywood | AS/NZS 2269 : 2012 - Plywood Structural | A Bond | Super E0 |
| Plywood | AS/NZS 2270 : 2006 - Plywood Interior | C Bond | E0 |
| Plywood | AS/NZS 2271 : 2004 - Plywood Exterior | A Bond | Super E0 |
| Plywood | AS/NZS 2272 : 2006 - Plywood Marine | A Bond | Super E0 |

Sime Due

Simon Dorries EWPAA General Manager Date of Issue :23-Mar-15

*Emission Limits : E0 <= 0.5mg/L, E1 <= 1mg/L, E2 <= 2mg / L. Super E0 must have an average emission amount <= 0.3 mg/L with a maximum amount <= 0.4 mg/L. For all standards other than AS/NZS 2269, the Super E0 classification is an industry limit. When Super E0 is claimed, the product also complies with the E0 classification from the relevant standard. This certificate is valid on the date of issue. This certificate must not be reproduced except in full. To view the current list of EWPAA certifications held by this organisation, please visit the EWPAA's on-line register at http://www.ewp.asn.au/register.

