

Plytech Keruing Multiply

Plytech Keruing Multiply is manufactured from 100% rotary cut Keruing veneer featuring an attractive and bold irregular grain pattern. Plytech Keruing Multiply is available in 28mm thickness made up of 19 veneer laminates. The multi-ply construction allows for the sheet edges to be used as a design feature. Clear finishing of the Keruing Multiply enhances the rich reddish-brown colour.



Applications:

Flooring applications, bench and bar-tops, shelvings and stairs. Also used in furniture construction, shop fit-outs and display cabinets.

Features:

Keruing Multiply is reddish-brown to dark brown in colour with an interlocked grain and a coarse texture.

Technical Specifications:

Standard – BS6566.

Faces – B/B

Wood Raw Material – Keruing

Density – average 850kg/m³

Class – Hardwood, moderately durable

Glue Bond – A bond Exterior Phenolic

Glue Formaldehyde Emission – E1.

Dimensions:

Thickness	Length x Width
28mm/19 ply	2440 x 1220m

Environment:

Glue formaldehyde emissions: CARB - Phase 2
LVLK Certification.

Handling and Storage:

Plywood is a natural product that can be affected by changes in ambient weather conditions, causing previously flat sheets to bow or twist. All precautions are taken to minimise this effect, however once the plywood has left our warehouse we cannot guarantee sheets to remain flat. This is particularly important where free standing kitchen/ cabinet doors are concerned.

For further information contact us on **0800 900 905**

While every endeavour has been made to ensure that all information contained in this product sheet is accurate, it is intended to be used as a guide line only. We reserve the right to amend specifications without notice. Product Warranty is as per our Standard Terms and Conditions of Trade. Please contact us for further detailed information.

plytech
CREATIVE STRENGTH