

# Plytech Soffitline

*Plytech Soffitline is manufactured exclusively from NZ Radiata Pine and has a warm wood character. Plytech Soffitline features a V-groove at 100mm centres to give the appearance of the traditional tongue and groove timber lining. Plytech Soffitline is H3.1 LOSP treated.*



## Applications:

Exterior soffit lining.

## Features:

Radiata Decorative is pale-yellow to pinkish-brown in colour with a figured grain and uniform texture.

## Technical Specifications:

Standard – AS/NZS 2271  
Wood Raw Material – Pinus Radiata  
Density – average 500kg/m<sup>3</sup>  
Class – Softwood, non-durable  
Glue Bond – A Bond Exterior  
Glue Formaldehyde Emissions E0 < 0.3mg/L  
(AS/NZS 2098.11).

## Environment:

E0: No harmful emissions  
FSC Certified.

## Dimensions:

2400 x 1200mm (Length x Width)
Thickness
7.5mm, 9.0mm, 12.0mm

## Handling and Storage:

Plywood is a natural product that can be affected by changes in ambient weather conditions, causing previously flat sheets to bow or twist. All precautions are taken to minimise this effect, however once the plywood has left our warehouse we cannot guarantee sheets to remain flat. This is particularly important where free standing kitchen/cabinet doors are concerned.

For further information contact us on **0800 900 905**

While every endeavour has been made to ensure that all information contained in this product sheet is accurate, it is intended to be used as a guide line only. We reserve the right to amend specifications without notice. Product Warranty is as per our Standard Terms and Conditions of Trade. Please contact us for further detailed information.

**plytech**  
CREATIVE STRENGTH