



## Product Specification

Product Name: **PORTER'S ULTRA FLAT ACRYLIC**

---

### PRODUCT DESCRIPTION:

Porter's Ultra Flat Acrylic is a superb quality ultra matt acrylic paint that is designed to give a long lasting elegant finish with superior coverage (even in deep base) and beautiful depth of colour. The ultra matt finish plays down surface imperfections due to less reflection, as well as accentuating depth of colour. Suitable for use on ceilings. This product is UV resistant, mark resistant with low odour.



APAS\* Target level for this product: 5g/L.

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

Porter's Ultra Flat Acrylic has met the assessment criteria set by Ecospecifier™ and is therefore eligible for Green Star credits. Please refer to [www.ecospecifier.com.au](http://www.ecospecifier.com.au) for further details.

The following descriptors have been adopted by APAS:

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

\* Australian Paint Approval Scheme.

### LOCATION:

Interior and exterior.

### ENVIRONMENTAL INFORMATION:

This product contains: <5g/L VOC's untinted (Volatile Organic Compounds contribute to atmospheric pollution. (Except Red base at 15.46 g/L).

### SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, masonry and previously painted surfaces.

## COLOURS:

Choose from our large range of colours, or ask our colourist for your own custom colour.

## LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C.

## PREPARATION:

### NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould. Dust down before proceeding.

On new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and repaired areas with Porter's Limeproof Undercoat Sealer, then apply two coats of same to entire area.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Limeproof Undercoat Sealer. Touch dry 2 hours. Allow 6 hours dry time.

### PREVIOUSLY PAINTED SUBTRATES:

Provided the surface is clean and sound, Porter's Ultra Flat Acrylic is self-priming and can be applied directly over previously painted surfaces. (Except oil-based paints or polyurethanes). High gloss paints or varnishes should be sanded to remove gloss and create a "keyed" surface. Previously painted surfaces with loose, peeling or

flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Porter's Limeproof Undercoat Sealer, then apply one coat to entire area. Touch dry 2 hours. Allow 6 hours dry time.

All varnishes, polyurethanes or surfaces previously painted with oil-based enamel paint should be thoroughly sanded to remove gloss and to create a "keyed" surface. Loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Porter's Universal Primer, then apply one coat of same to entire area. Touch dry 2 hours. Allow 6 hours dry time between coats and 24 hours dry time.

## APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush, spray or a medium nap roller. Touch dry in 1 hour. Allow minimum 2 hours dry time between coats. Allow 6 hours dry time.

## COVERAGE RATES:

Covers approximately 14-16m<sup>2</sup> per litre, depending upon porosity, surface texture and wastage rates.

## WASH UP:

Water.

## COMPLEMENTARY PRODUCTS:

Porter's Limeproof Undercoat Sealer (coverage 12m<sup>2</sup> per litre) is recommended where an undercoat/primer is required when preparing substrate for painting.

Mineral Silicate Primer (coverage 10m<sup>2</sup> per litre) is recommended for priming new set plaster before undercoating.

Porter's Universal Primer (coverage 10m<sup>2</sup> per litre).

## PACKAGING:

Porter's Ultra Flat Acrylic is available in 1 litre, 4 litre, 10 litre & 15 litre sizes.

## STORAGE:

Store in a cool dry area, protected from frost.

## PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

## WARRANTY:

**15 YEAR GUARANTEE:** Porter's Paints Ultra Flat Acrylic is guaranteed against peeling, flaking and blistering on external applications for 15 years if applied according to the specified instructions. This guarantee applies to residential work only

and does not cover paint failure caused by any breakdown of coatings applied previously, where Porter's Paints Ultra Flat Acrylic is applied over coatings not specified by Porter's Paints or in the event of substrate failure. If the product does not perform as specified, we will replace the goods free of charge.

The warranty above applies for 15 years from the date of purchase. To make a claim under the warranty, please contact Porter's Paints using the details shown and provide details of your claim. You must show proof of purchase and bear all expenses incurred in making a claim. The benefits of this warranty are in addition to other rights and remedies under any applicable law.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

## MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints  
288 Coward St  
Mascot NSW 2020  
Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)

Web: [www.porterspains.com](http://www.porterspains.com)

Porter's Paints

150 Hutt Park Rd  
Gracefield  
Lower Hutt 5010  
New Zealand  
Ph: 0800 672 468