



Product Specification

Product Name:

PORTER'S CLEARCOTE

PRODUCT DESCRIPTION:

Porter's heavy duty Clearcote is a low odour, fast drying, water-based clear finish suitable for a variety of interior and exterior surfaces. Porter's Clearcote is exterior durable, has excellent UV stability and resists yellowing.

The following descriptors have been adopted by APAS:

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

* Australian Paint Approval Scheme.

LOCATION:

Interior or exterior.

SUGGESTED APPLICATIONS:

Suitable for use on a wide variety of substrates, including any interior timber that requires sealing and protection. Ideal for interior wooden or concrete floors, furniture and, kitchen cupboards.

ENVIRONMENTAL INFORMATION:

This product contains: 24g/L VOC's (Volatile Organic Compounds contribute to atmospheric pollution.

APAS* Target level for this product: 500g/L.

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

COLOUR AND FINISH:

Appears milky white in can, dries clear.

Dries to a low lustre finish.

LIMITATIONS:

Not suitable for use over Porter's Milk Paint, Porter's Fresco or previously oiled timbers or

timbers that are oily in nature*. Not suitable on **exterior** timber surfaces.

Kitchen and bathroom bench tops: May be subject to staining if used on timber bench tops where there will be heavy soiling from oil, food and make up.

Not recommended as a sealer for floor tiles as they may become slippery when wet.

Important information about damp substrates:

Concrete slabs can be affected by condensation, moisture migration through the concrete from the soil underneath, broken or leaking pipes under the concrete, surface water leaks or flooding. Wooden interior floors can be affected by flooding, improper cleaning, cracks in foundations, or liquid spills. All these scenarios are the enemy of paints and clear coatings, and all sources of dampness (hydrostatic pressure), not only on the surface, but through the entire substrate, must be eliminated and the substrate thoroughly dried throughout prior to applying Clearcote. Applying Clearcote onto a damp substrate will prevent film cure, and will cause the Clearcote to appear cloudy and delaminate (peel off).

Test before use on timber with a high tannin content. Normally tannin bleed is undetectable, but if you are using Clearcote over a finish such as Wood Wash tannin bleed may be visible as a slight brown staining. Tannin bleed does not affect product performance. Porter's Tannin Block should be considered to prevent this problem, and should be applied over the Wood Wash, and prior to application of Clearcote.

****Important information about timber:***

Not suitable for use over timbers that are oily in nature, such as brush box, blackbutt, jarrah, spotted gum, teak and other hardwoods that have

a natural oiliness or waxiness. These timbers should be well aged and allowed to dry out to allow the Clearcote to penetrate, otherwise the natural oils in the timber will repel the water-based Clearcote causing lack of adhesion, resulting in peeling and delamination.

Not suitable for exterior decking, due to the high oil content in decking timbers. refer to our website for a more suitable product.

Always test prior to use. Do not apply in high humidity, below 10 °C or above 30 °C. Note that this also applies to the *surface temperature* of the substrate. If applied to a surface that is hot from the sun, Clearcote may dry too fast and not cure correctly and this may result in loss of adhesion, cracking and therefore allow the ingress of moisture.

Not suitable for spraying.

PREPARATION:

The substrate should be a clean well-held surface free from loose material, dirt, dust, grease, oil and mould. Dust down before proceeding. Allow all paints and finishes to dry a minimum of 72 hours prior to the application of Porter's Clearcote. When being applied as a floor sealer, vacuum prior to application.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush or lambs' wool applicator (recommended for floors). Touch dry in 30 minutes. Allow minimum 2 hours dry time between coats. Hard dry in 2 hours. Sand lightly between coats to remove any raised grain. Vacuum to remove dust before

applying another coat. Allow 4-6 hours before allowing light foot traffic on floor surfaces. Full cure is achieved in 2 days. On exterior surfaces protect from rain for 3 days. Not suitable for spraying.

COVERAGE RATES:

Covers approximately 15m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Clearcote is compatible for use over Porter's Wood Wash and Porter's Concrete Wash. Test before use as a slight colour variation may occur.

PACKAGING:

Porter's Clearcote is available in 1 litre, 4 litre, 10 litre & 15 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints
288 Coward St
Mascot NSW 2020
Australia
Phone: (02) 9698-5322
Toll free: 1800 656 664
Fax: (02) 9699-5322
NZ Customer Service: 0800 672 468
E-mail: enquiries@porters.com.au
Web: www.porterspains.com

Porter's Paints
150 Hutt Park Rd
Gracefield
Lower Hutt 5010
New Zealand
Ph: 0800 672 468