



Product Specification

Product Name:

PORTER'S CEILING FLAT

PRODUCT DESCRIPTION:

Porter's Ceiling Flat is a quick drying acrylic paint designed for interior ceilings. Made with concentrated titanium pigment, Porter's Ceiling Flat provides ultimate hiding power and its flat finish helps to cover surface imperfections for that perfectly even finish, and the ultra white colour maximizes light just where it is needed. As ceilings are "low traffic" areas, it is common for paint companies to use the cheapest, lowest performing paint resins, but Porter's Ceiling Flat is formulated for a high performance finish that lasts. Porter's Ceiling Flat is easy to use – it has a low odour, low spatter formulation that glides on easily, its creamy consistency making application easy.

Porter's Ceiling Flat is super bright white in colour, creating a clean, spacious feel and maximizing light. Dries to a matt finish.

LOCATION:

Interior

ENVIRONMENTAL INFORMATION:

This product contains: 47.16g/L VOC's. (Volatile Organic Compounds contribute to atmospheric pollution.

APAS* Target level for this product: 50g/L.

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

The following descriptors have been adopted by APAS:

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

* Australian Paint Approval Scheme.

SUGGESTED APPLICATIONS:

Can be applied to suitably prepared plasterboard or set plaster, interior only.

COLOURS:

Supplied as bright white, ready to use. Matt finish.

LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C.

Not recommended for use on floors and walls.

Not recommended for bathrooms and high humidity areas.

PREPARATION:

NEW/UNPAINTED CEILINGS:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould. Dust down before proceeding.

On new unpainted plasterboard sheeting, spot prime all joints and repaired areas with Porter's Limeproof Undercoat Sealer, then apply two coats of same to entire area.

On new unpainted concrete must be cured for a minimum of 30 days prior to priming, the surface must be sanded, washed and allow dry to remove any release agents or loose friable material. Prime with two coats of Porter's Lime Proof Undercoat.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Limeproof Undercoat Sealer. Touch dry 2 hours. Allow 6 hours dry time.

PREVIOUSLY PAINTED CEILINGS:

Provided the surface is clean, dry and free from loose friable material and any contaminants that it is likely to compromise adhesion, Porter's Ceiling Flat is self-priming and can be applied directly over previously painted surfaces. (only over waterbase acrylics and PVA only)

Surfaces painted with oil-based paints: surfaces with loose, peeling or flaking paint must be made sound by scraping off and removing all loose and friable material, gloss finishes must be sanded. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Porter's Universal Primer, then apply one coat to entire area. Touch dry two hours. Allow 6 hours dry time.

APPLICATION:

Stir thoroughly prior to use and occasionally during application. Apply two coats by medium nap synthetic roller, brush or airless spray*. Touch dry in 30 minutes. Allow minimum 2 hours dry time between coats. Full cure is achieved in 7 days.

*Pressure 2000 psi, tip 0.015" - 0.021"

COVERAGE RATES:

Covers approximately 12m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Limeproof Undercoat Sealer (coverage 12m² per litre) is recommended where an undercoat/primer is required when preparing substrate for painting.

Mineral Silicate Primer (coverage 10m² per litre) is recommended for priming new set plaster before undercoating.

Porter's Universal Primer (coverage 12m² per litre) A tough all-purpose primer for use when extra masking or isolation of substrate is required, or for transitioning from an oil based enamel paint to a water based acrylic paint.

PACKAGING:

Porter's Ceiling Flat is available in 4L, 10L and 15L sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints
288 Coward St
Mascot NSW 2020
Australia
Phone: (02) 9698-5322
Toll free: 1800 656 664
Fax: (02) 9699-5322
E-mail: enquiries@porters.com.au
Web: porterspains.com

Porter's Paints
150 Hutt Park Rd
Gracefield
Lower Hutt 5010
New Zealand
Ph: 0800 672 468