



Product Specification

Product Name:

PORTER'S CHALKBOARD PAINT

PRODUCT DESCRIPTION:

Porter's Chalkboard Paint is perfect for making your own chalkboards in cafés, kitchens, workplaces and children's play areas. Available in two bases, traditional Black, and also Ultra Deep for a fun range of bright bold colours. Dries to a smooth finish for easy cleaning. Has a superb creamy texture with excellent coverage.

LOCATION:

Interior or exterior.

ENVIRONMENTAL INFORMATION:

This product contains: ≤ 29.74 g/L VOC's (Volatile Organic Compounds contribute to atmospheric pollution.

APAS* Target level for this product: 100g/L.

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

The following descriptors have been adopted by APAS:

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

* Australian Paint Approval Scheme.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, masonry and previously painted surfaces.

COLOURS:

Choose from our large range of colours, or ask our colourist for your own custom colour.

LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mould.

Dust down before proceeding.

On bare surfaces such as new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and repaired areas with Porter's Limeproof Undercoat Sealer, then apply two coats of same to entire area.

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Limeproof Undercoat Sealer. Touch dry 2 hours. Allow 6 hours dry time.

PREVIOUSLY PAINTED SUBTRATES:

Provided the surface is clean and sound, Porter's Chalkboard Paint can be applied directly over previously painted surfaces.

Previously painted surfaces with loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Porter's Limeproof Undercoat Sealer, then apply one coat to entire area. Touch dry two hours. Allow 6 hours dry time.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush or a medium nap roller. Touch dry in 30 minutes. Allow minimum 2 hours dry time between coats. Allow 48 hours dry time before use as a chalkboard.

CARE OF YOUR CHALKBOARD

Chalk can be removed with ordinary blackboard dusters, however, for best results clean with a damp sponge or rag.

COVERAGE RATES:

Covers approximately 10m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Limeproof Undercoat Sealer (coverage 12m² per litre) is recommended where an undercoat/primer is required when preparing substrate for painting.

Mineral Silicate Primer (coverage 10m² per litre) is recommended for priming new set plaster before undercoating.

PACKAGING:

Porter's Chalkboard Paint is available in 500ml & 1 litre & 4 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing.
Avoid eye contact. Avoid prolonged skin contact.
Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints
288 Coward St
Mascot NSW 2020
Australia
Phone: (02) 9698-5322
Toll free: 1800 656 664
Fax: (02) 9699-5322
E-mail: enquiries@porters.com.au
Web: www.porterspains.com

Porter's Paints
150 Hutt Park Rd
Gracefield
Lower Hutt 5010
New Zealand
Ph: 0800 672 468