



Product Specification

Product Name: **PORTER'S CEMENT CRACK SEALER**

PRODUCT DESCRIPTION:

Porter's Cement Crack Sealer is for use prior to painting over new cement render or bagging that shows non-structural hairline cracking. Designed to bridge cracks up to 0.3mm. Remains flexible throughout its life.

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

* Australian Paint Approval Scheme.

LOCATION:

Exterior

CHECKING FOR HAIRLINE CRACKING:

Cement renders are occasionally subject to hairline cracking (caused by drying too fast). To test for hairline cracking hose down the cement render/bagging, and as it dries any cracks in the cement rendered surface will become evident.

ENVIRONMENTAL INFORMATION:

This product contains: 1.89g/L VOC's (Volatile Organic Compounds contribute to atmospheric pollution.

APAS* Target level for this product: 60g/L.

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

The following descriptors have been adopted by APAS:

SUGGESTED APPLICATIONS:

For use, prior to painting, over new cement render or bagging that shows non-structural hairline cracking.

COLOUR:

Appears milky white in can, dries clear.

LIMITATIONS:

Not suitable for use over previously painted surfaces. This product is designed for use under Boncote® Cement Paint only. Contact Porter's Technical Department for advice on surface preparation over hairline cracking when using other paint types. Do not apply in high humidity, below 10 °c or above 30 °c.

PREPARATION:

The substrate should be a clean well-held surface free from loose material dirt, dust, grease, oil and mould. Allow rendered or bagged surfaces to cure for a minimum of 28 days prior to application.

APPLICATION:

Stir thoroughly prior to use. Apply one coat by brush or roller to entire wall surface, edge to edge. Allow to dry overnight. Remains tacky until top coated.

COVERAGE RATES:

Covers approximately 12-14m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Cement Crack Sealer is suitable for use prior to painting with Boncote® Cement Paint only.

PACKAGING:

Porter's Cement Crack Sealer is available in 1 litre & 4 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints
288 Coward St
Mascot NSW 2020
Australia
Phone: (02) 9698-5322
Toll free: 1800 656 664
Fax: (02) 9699-5322
NZ Customer Service: 0800 672 468
E-mail: enquiries@porters.com.au
Web: www.porterspains.com

Porter's Paints
150 Hutt Park Rd
Gracefield
Lower Hutt 5010
New Zealand
Ph: 0800 672 468