EXTERNAL WALL Wall frame (Timber or Steel) Wall bottom plate fixed to Bottom plate SPEEDFLOOR joists with 1/M12 (Timber or Steel) bolt with 50mm washer, at 900c/c overall or to engineers Timber flooring, glued and specification (within 300mm of all screwed to SPEEDFLOOR external corners and openings, joists with 10-10x50 csk and within 100mm of all bracing wingtek screws panels). SPEEDFLOOR Floor joist, fixed to SPEEDFLOOR boundary joist with 3/10-16x16 hex head Boundary floor joist, screws per tab fixed to top plate with 1/M12x80 bolt with washer @900c/c **#**#T, Steel ceiling battens, fixed with 2/16-16x16 screws at each Top plate packer as required intersection, or fixed with or specified. ceiling clips Wall frame (Timber or Steel)

MFD 1B - SPEEDFLOOR 240 or 290 Joist to Wall Frame

	Speedfloor	Mail: P.O. Box5420 Wellesley St Auckland NZ	Standard Details	Title Speedfloor 240 or 290 Joist to Wall Frame	Scale 1:10 @ A4	Rev A	Sheet
		PH: +64 9 303 4825 www.speedfloor.co.nz			Drawn by EO	Date 15/09/2015	MFD 1B