

**Declaration of performance N. CPR-IT4/ B0013 rev. 17/04/2019**

- 1) Unique identification code of the product-type: **ADESOGUARD SA**
- 2) Intended uses: **Bitumen damp proof sheets including bitumen basement tanking sheets -TYPE A-**
- 3) Manufacturer: **POLYGLASS S.P.A Via Dell'Artigianato, 34-31047 Ponte di Piave (TV) ITALIA - [www.polyglass.com](http://www.polyglass.com)**
- 4) System of VVCP: **System 2 +**
- 5) Harmonized standards: **EN 13969:2004 + A1:2006**  
Notified bodies:  
**The Notified Body BUREAU VERITAS, N. 1370 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of conformity of the factory production control.**

6) Performances declared:

Essential characteristics	Performances
Reaction to fire	<b>NPD</b>
Watertightness (Method B)	<b>Meet requirements</b>
Tensile properties Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	<b>500/400 (±20%) N/50 mm 100/100 (±15) %</b>
Resistance to static loading (Method A)	<b>≥ 5 Kg</b>
Resistance to impact (Method A)	<b>≥ 300 mm</b>
Resistance to tearing (longitudinal/transverse)	<b>200/200 (±30%) N</b>
Joint strenght Shear resistance	<b>400/300 (±20%) N/50 mm</b>
Durability watertightness: Against artificial ageing Against chemicals	<b>Meet requirements Meet requirements</b>
Flexibility at low temperature	<b>≤ -25 °C</b>
Dangerous substances	<b>NPD</b>

This is an article in accordance with Article 3 of the REACH regulation (EC) no. 1907/2006 and pursuant to Article 31 and 33 of the a/m regulation does not require any Safety Data Sheet. While using the product, pay attention to the recommendations written in the Technical Data Sheet and to the safety requirements laid down in the workplace

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Ing. P. Ciferri**

**In Ponte di Piave 17/04/2019**



.....  .....

*DoP in Pdf format are available in the Polyglass SpA website.*

Version 1:	Unchanged product, DoP layout updated
------------	---------------------------------------



ADESOGUARD SA  
 CE MARKING  
 Annex to DoP N. CPR-IT4/ B0013  
 rev. 17/04/2019

 1370	 Via Dell'Artigianato, 34 31047 Ponte di Piave (TV) ITALIA - <a href="http://www.polyglass.com">www.polyglass.com</a>
14 CPR-IT4/ B0013 rev. 17/04/2019 EN 13969 ADESOGUARD SA <i>Bitumen damp proof sheets including bitumen basement tanking sheets - TYPE A-</i>	
Watertightness (Method B)	Meet requirements
Tensile properties	
Tensile strength (longitudinal/transverse)	500/400 (±20%) N/50 mm
Elongation (longitudinal/transverse)	100/100 (±15) %
Resistance to static loading (Method A)	≥ 5 Kg
Resistance to impact (Method A)	≥ 300 mm
Resistance to tearing (longitudinal/transverse)	200/200 (±30%) N
Joint strenght	
Shear resistance	400/300 (±20%) N/50 mm
Durability:	
Against artificial ageing	Meet requirements
Against chemicals	Meet requirements
Flexibility at low temperature	≤ -25 °C
Dangerous substances	NPD

**Note:**

*Polyglass supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:*

- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*