## RESIDENTIAL SLIMCLAD REVERSE RUN WALL CLADDING METER BOX SIDE FLASHING FOR HORIZONTAL CLADDING

Detail Number: RI-RSCW041A

Date drawn: 25/11/2021

Scale: 1:5@, A4

BUILDING WRAP DRESSED INTO WATERPROOF AIRSEAL TO OPENING AS PER E2/AS I PERIMETER OF TRIM CAVITY ROOFING INDUSTRIES BACK TRAY\* FLASHING RUN FROM TOP OF HEAD FLASHING TO GROUND OR EXIT POINT ROOFING INDUSTRIES STOP FND 'SLIMCLAD REVERSE RUN' PROFILED METAL CLADDING SEPARATION OF BATTEN -60 mm min. AND METAL CLADDING MFTFR BOX SCREW FIXING (3) -SEAL AND RIVET 40x40 PREFINISHED STEEL ANGLE PROFILED CLOSED CELL FOAM SFT IN SFALANT

SLIMCLAD REVERSE RUN IS OUTSIDE THE SCOPE OF E2/AS I BUT MAYBE APPLICABLE FOR NON RESIDENTIAL BUILDINGS OR AS AN ALTERNATIVE SOLUTION

## NOTES:

- These details are to be read with Roofing Industries profile technical summary regarding wind loads and fixings.
- These details are generally in compliance E2/AS I and/or the NZ Metal Roof \$ Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'.
- The building designer is ultimately responsible to ensure that details used meet the requirements of the NZ Building Code for the specific project.
- Details of the supporting structure including cavity batters are indicative only and are the responsibility of the building designer. For steel framed buildings thermal break cavity batters may be required.
- Roof/Wall underlay selection are the responsibility of the designer. Underlay to be installed in accordance with underlay manufacturer's recommendations and requirements.
- These details are for Roofing Industries profile/s as nominated and may not be applicable to other profiles.
- This drawing is the copyright of 'Roofing Industries' and can only be copied or reproduced with their permission.
- Further information can be obtained from the NZ Metal Roof \$ Wall Cladding Code of Practice: www.metalroofing.org.nz or E2/AS1.
- Details are for steel based materials, other substrates may require some changes.
- All dimensions are nominal.

## DETAIL ANNOTATION:

- CAVITY BATTENS CONTAINING CORROSIVE
   MATERIAL MUST BE SEPARATED FROM METAL
   CLADDING BY DPC, BUILDING WRAP, PVC OR
   PAINTING
- 2. REFER TO E2/AS I FOR GENERAL METERBOX AND SIMILAR PENETRATIONS/OPENINGS
- 3. FASTENERS TO BE COMPATIBLE WITH
  MATERIAL BEING FIXED AND THE SUITABLE
  GRADE FOR THE ENVIRONMENT IN WHICH
  LOCATED

METER BOX SIDE FLASHING

\* Back tray size may require to increase to ensure coverage at ends of head

flashing. Turn down end of head flashing

Copyright detail © 2021

