

Dekton®

1. Identification of the article and of the company/undertaking

Name of Material: Dekton®

Use of Material: Ultra-compact surface designed for use indoors and outdoors, particularly kitchen and bathroom worktop, flooring, cladding and facades.

Avoided uses: Do not elaborate the material by dry processes.

Name of the company:

COSENTINO, S.A. Ctra. A-334. Km 59
Cantoria (Almería) Spain
Telephone: +34 950 44 41 75 / Fax: +34 950 44 42 26
www.cosentino.com

Person in charge of MSDS,
Maria Gonzalez Contreras; imgonzalez@cosentino.com

Phone number in case of emergency:
Toxicology Helpline: +34 91 562 04 20

2. Hazards identification

There is no provision for any risk associated with the finished Dekton® material in the CLP (EC) regulation nº. 1272/2008. However respirable crystalline silica dust can be generated in manufacturing operations. Respirable crystalline silica causes harm to the lungs, such as silicosis, through prolonged or repeated exposure (Hazard H372). A series of preventative measures should be adopted to prevent or minimise exposure.

Contents of crystalline silica < 11%.



HAZARD

H 372 Causes damage to lungs through prolonged or repeated exposure (inhalation).



Classification according to directive 1999/45/EC
R20 Harmful by inhalation
R48 Danger of serious damage to health by prolonged exposure.

PREVENTION



P260 Do not breathe dust generated in the cutting, grinding and polishing processes.

P264 Wash face and hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this material.

P 284 Wear respiratory protection for particles (P3).

FIRST AID MEASURES

P314 W Get medical advice/attention if you feel unwell.

P 501 Dispose of remains in accordance with local regulation.

S22 Do not breath the dust.

S38 W Use personal protective equipment P3.

3. Composition/information on ingredients

Composition (%):

Dekton® is made up of silicoaluminates, amorphous silica, crystalline silica, zircon and inorganic pigments. The composition of crystalline silica (SiO₂) is below 11%.

CRYSTALLINE SILICA - QUARTZ:
CAS 14808-60-7 / EINECS 238-878-4

4. First aid measures



The finished material do not required special measures. Following is for the process of fabrication:

Contact with eyes: Keep your eyes open and wash thoroughly with lots of water.

Contact with skin: Wash with soap and water.

Inhalation: Bring the affected employee to a well-ventilated place. Additional ventilation may be required if the employee has suffered a serious reaction. Properly ventilate the work area. Seek medical advice if you feel unwell.

5. Firefighting Measures

Fire-resistant: Category: A1 / A1fl

Suitable extinguishing agents: Any suitable agent for surrounding fires. Extinguishers of polyvalent powder are recommended.

Personal Protection Equipment: Depending on the surrounding fire.

6. Accidental release measures

The material does not represent risk of spillage.

7. Handling and storage

Manual handling.

The user has the responsibility to carry out a risk evaluation according to the local risk prevention law. We recommend the following precautions:

- Safe manipulation systems should be used (crane, A-frame with safety bars). The slings must be well protected/resistant as the material is more cutting than natural stone.
- Use following Personal Protective Equipment. Wear helmet, safety shoes, safety glasses, and gloves during the handling and storage operations of Dekton.

Environmental protection precautions. We recommend the use of water-cooled tools to prevent the creation of dust.

Storage.

There are no specific conditions for safe storage, except that it should be properly stored in a closed and covered place. Avoid strong impacts that may cause the material to break.

8. Exposure controls / personal protection

Exposure limit values.

The user has the responsibility to carry out a risk evaluation of dust exposure according to the local risk prevention law.

**Occupational Exposure Limits in mg/m³
8 hours TWA - Respirable dust - in EU 271
+ Norway & Switzerland**

COUNTRY/AUTHORITY	INERT DUST	QUARTZ (Q)	CRISTOBALITE (C)	TRIDYMITTE (T)
Austria / I	6	0,15	0,15	0,15
Belgium / II	3	0,1	0,05	0,05
Bulgaria / III	4	0,07	0,07	0,07
Cyprus / IV	/	10 Kg/Q ²	/	/
Czech Republic / V		0,1	0,1	0,1
Denmark / VI	5	0,1	0,05	0,05
Estonia		0,1	0,05	0,05
Finland / VII		0,2	0,1	0,1
France / VIII		5 or 25 k/Q		
France / IX	5	0,1	0,05	0,05
Germany / X	3	/ ³	/	/
Greece / XI	5	0,1	0,05	0,05
Hungary		0,15	0,1	0,1
Ireland / XII	4	0,05	0,05	0,05
Italy / XIII	3	0,025	0,025	0,025
Lithuania / XIV	10	0,1	0,05	0,05
Luxembourg / XV	6	0,15	0,15	0,15
Malta / XVI ⁴	/	/	/	/
Netherlands / XVII	5	0,075	0,075	0,075
Norway / XVIII	5	0,1	0,05	0,05
Poland		0,3	0,3	0,3
Portugal / XIX	5	0,025	0,025	0,025
Romania / XX	10	0,1	0,05	0,05
Slovakia		0,1	0,1	0,1
Slovenia		0,15	0,15	0,15
Spain / XXI	3	0,05	0,05	0,05
Sweden / XXII	5	0,1	0,05	0,05
Switzerland / XXIII	6	0,15	0,15	0,15
United Kingdom / XXIV	4	0,1	0,1	0,1

¹ Missing information for Latvia. - To be completed.

² Q : quartz percentage - K=1

³ Germany has no more OEL for quartz, cristobalite, tridymite. Employers are obliged to minimize exposure as much as possible, and to follow certain protective measures.

⁴ When needed, Maltese authorities refer to values from the UK for OELs which do not exist in the Maltese legislation.

COUNTRY	ADOPTED BY/LAW DENOMINATION	OEL NAME (IF SPECIFIC)
Austria / I	Bundesministerium für Arbeit und Soziales.	Maximale ArbeitsplatzKonzentration (MAK)
Belgium / II	Ministere de l'Emploi et du Travail.	
Bulgaria / III	Ministry of Labour and Social Policy and Ministry of Health. Ordinance n°13 of 30/12/2003.	Limit Values
Cyprus / IV	Department of Labour Inspection. Control of factory atmosphere and dangerous substances in factories, Regulations of 1981.	
Czech Republic / V	Governmental Directive n°441/2004.	
Denmark / VI	Direktoratet for Arbejdstilsynet.	Threshold Limit Value
Finland / VII	National Board of Labour Protection.	Occupational Exposure Standard
France / VIII	Ministère de l'Industrie (RGIE).	Empoussiérage de référence
France / IX	Ministère du Travail.	Valeur limite de Moyenne d'Exposition
Germany / X	Bundesministerium für Arbeit.	Maximale ArbeitsplatzKonzentration (MAK)
Greece / XI	Legislation for mining activities.	
Ireland / XII	2002 Code of Practice for the Safety, Health & Welfare at Work (CoP).	
Italy / XIII	Associazione Italiana Degli Igienisti Industriali.	Threshold Limit Values (based on ACGIH TLVs)
Lithuania / XIV	Del Lietuvos higienos normas HN 23:2001.	Ilgalaikio poveikio ribine verte (IPRV)
Luxembourg / XV	Bundesministerium für Arbeit.	Maximale ArbeitsplatzKonzentration (MAK)
Malta / XVI ⁴	OHS –LN120 z 2003 r., www.ohsa.org.mt	OELVs
Netherlands / XVII	Ministerie van Sociale Zaken en Werkgelegenheid.	Publieke grenswaarden http://www.ser.nl/en/oel_database.aspx
Norway / XVIII	Direktoratet for Arbejdstilsynet.	Administrative Normer (8hTWA) for Forurensing i Arbeidsmiljøet
Portugal / XIX	Instituto Portuges da Qualidade, Hygiene & Safety at Workplace NP1796:2004.	Valores Limite de Exposição (VLE)
Rumunia / XX	Government Decision n° 355/2007 regarding workers' health surveillance. Government Decision n° 1093/2006 regarding carcinogenic agents (in Annex 3: Quartz, Cristobalite, Tridymite).	OEL
Spain / XXI	Instrucciones de Técnicas Complementarias (ITC) Orden ITC/2585/2007	Valores Limites
Sweden / XXII	National Board of Occupational Safety and Health	Yrkeshygieniska Gransvariden
Switzerland / XXIII		Valeur limite de Moyenne d'Exposition
United Kingdom / XXIV	Health & Safety Executive	Workplace Exposure Limits

Source: IMA-Europe. Date: May 2010, updated version available at <http://www.ima-europe.eu/otherPublications.html>

Exposure Controls. Manufacturing and installation.

The manufacturer recommends methods that involve the use of water in the manufacturing of this material. Dust derived from the manufacturing processes could contain respirable crystalline silica (SiO₂).

Long term exposure to dust derived from the cutting and manufacturing processes without the use of suitable protection may cause serious diseases including pneumoconiosis such as silicosis, as well the deterioration of other lungs diseases such as bronchitis, emphysema, etc.

Exposure to dust may be monitored and controlled with suitable control measures such as:

- Prevent or minimise dust generation. In manufacturing operations use equipment provided with water supply system. The water should be clean, abundant and directed to the points of cutting, grinding and polishing.
- Prevent or minimise dust being released into the environment. Use dust extraction systems in the area where it is generated.
- Indicate and demarcate hazard areas.
- Perform periodic control of the environmental concentration of respirable crystalline silica.
- Natural and/or mechanical ventilation systems that ensure the renewal of air in the work place.
- Cleaning and maintenance. Use of vacuum and/or water

cleaning systems, avoid sweeping and the use of compressed air, which creates dust. Preventive maintenance programmes of the installations to ensure the correct conditions of order, cleaning and operation of work equipment.

- Always use respiratory protection for P3 type particulates according to EN 143:2001 and its revisions EN 143/AC 2002, EN 143/AC 2005, including working with water as a dust-reducing agent during the preparation of Dekton®.
- Hand Protection. Use gloves to avoid the risk of cutting when handling pieces.
- Eye protection. Use eye protection in accordance with regulation EN166:2001.
- Skin protection. We recommend that work clothes are worn to avoid the contact of dust with skin. Wash hands and face with soap and water to remove dust before breaks and at end of the shift.
- Work clothes: do not clean up using compressed air, use vacuum cleaning methods.
- Do not eat or drink in work areas.
- Change out of work and/or protective uniform and clean oneself up before eating lunch.
- At the end of the working day, clean oneself up, shower if necessary change into clean clothes before leaving work.
- Establish a specific health monitoring system
- The parts must leave the workshop totally finished and ready to be installed by the installer.

9. Physical and chemical properties

Apect: Solid, according to commercial range.

Colour: commercial range.

Odour: Odourless.

pH: N/A.

Miscibility (in water): N/A.

Water absorption (ISO 10545-3): -0,05%.

Density: 2400-2600 kg/m³

Compression resistance (EN-14617-15): 112-248 MPa.

Bending stress (ISO 10545-4): ≥ 50 MPa

Autoignition temperature: N/A.

Fire point: N/A.

10. Stability and reactivity

Conditions to avoid:

- Avoid contact with surfaces at temperatures above 300 ° C.
- Avoid strong impacts that may cause the material to break.

Decomposition products: Unknown.

11. Toxicological information

Toxicological Helpline (Spain): +34 91 562 04 20

Dust derived from the manufacturing processes could contain respirable crystalline silica (SiO₂).

Long term exposure and/or mass fraction of respirable crystalline silica may cause severe damage to health including pulmonary fibrosis and pneumoconiosis such as silicosis, as well the deterioration of other lungs diseases such as bronchitis, emphysema, etc. The main symptom of silicosis is the reduced capacity of the lung. Persons affected by silicosis have a higher risk of suffering from lung cancer.

12. Ecological information

Dekton® does not contain ecotoxins.

13. Disposal considerations

In accordance with European Directives 91/156/EEC and 199/31/CEE and the law 10/98, April 21 and RD 1481/2001, 27 December, a product that does not meet quality specifications or is rejected can be disposed off at inert waste landfills. The Dekton® packaging will be disposed off according to country regulations. In general, they will be deposited in plastic or paper containers depending on whether or not it can be recycled.

14. Transport information

The material is not classified as dangerous according to air, land and sea transport regulations.

UN NUMBER	UNASSIGNED	SEA TRANSPORT	
Packaging group	none	IMDG/IMO	no restricted
ROAD AND RAIL TRANSPORT		AIR TRANSPORT	
ADR/RID		ICAO/ITA	no restricted
TPC/TPF	no restricted		

15. Regulatory information

This Safety Data Sheet (MSDS) has been prepared according to CLP Regulation, (EC) No 1272/2008.

Labelled according to European EEC directives.

16. Other information

Check with Cosentino, SA before using or supplying this material for other applications, different to those previously stated.

The information in this document is to our knowledge up-to-date and accurate. However, we cannot guarantee the recommendations or suggestions herein, as the material conditions of use are beyond our control. In addition, the contents of this safety data sheet must not be interpreted as a recommendation to use any product in violation of the laws, safety practices or patents in force on any material or its use.

It is the responsibility of the recipient of our material to check the corresponding rules and regulations. Under no circumstances does the data contained in this Safety Data Sheet constitute a guarantee of specific properties or create any contractual relationship.

This Safety Data Sheet (MSDS) is according to the CLP Regulation, (EC) No 1272/2008.

For further information follow the instructions in the Guide to Good Practice for Preparation published by the manufacturer. Information available www.dekton.com

You can get further information in <http://www.nepsi.eu/> and the Guide to Good Practice for the Agreement on Workers' Health Protection Through the Good Handling and Use of Crystalline Silica and Products Containing it, published by NEPSI.