

## Product Fact Sheet

# FirePro<sup>®</sup> 9300

Dulux FirePro<sup>®</sup> 9300 is a solventless, ultra-high build epoxy intumescent with the ability to provide up to 60 minutes of cellulosic fire protection in internal and external locations up to a C5 environment.



**Protection you can count on.**

# FirePro® 9300

## Solventless ultra high build epoxy intumescent coating

Dulux FirePro® 9300 is a solventless, ultra-high build epoxy intumescent with the ability to provide up to 60 minutes of cellulosic fire protection in internal and external locations up to a C5 environment.

**Features:**

- Exterior durable protection
- Resistant to handling damage
- Fast drying
- Solventless, low VOCs and low odour

**Benefits:**

- Offers fire and corrosion protection across a range of environments
- Transportable from shop to site
- Fast drying, fast to process

**Product overview**

Chemistry	Epoxy
Product type	Intumescent
Volume solids	100%
VOC level	<2 g/L
Dry film thickness (min-max)	300-2500µm
Cellulosic fire protection	Up to 60 minutes
Abrasion resistance	Good
Water resistance	Excellent



T 13 23 77

T 0800 800 424

[www.duluxprotectivecoatings.com.au](http://www.duluxprotectivecoatings.com.au)