

Facsimile

To:	Jason Bardell	From:	Doug Gaunt
Organisation:	IBS	Subject:	1200mm x 2.4m Wall (9.0mm Panelline/PLANKWALL V100)
Location:	Auckland	Date:	5 June 2019
Fax No.:	09 5740325	No. of	5
Tel No.:	09 5740314	Pages:	

Please call +64 7 343 5763 if transmission incomplete

Jason

Please find below the P21 test results of your three 1200mm x 2.4m walls constructed as follows:

- 90x45 SG8 studs (600 centres), plates and noggs
- 9.0mm Panelline/PLANKWALL V100 cladding one side only
- Panelline/PLANKWALL V100 fixed with 50x3.0 galvanised nails at 150mm centres to perimeter and at 300 centres to middle stud
- 25x0.9mm straps around bottom plate fixed to each side of end studs with six 30x2.5 galvanised clouts
- Tested on a 'concrete' floor with M12 hold down bolts & 50x50x3 washers

P21 bracing results

1. BU wind = 149 (124 BU/m) as limited by the serviceability load capacity
2. BU Earthquake = 161 (134 BU/m) as limited by the ultimate load capacity.

Figures 1, 2 & 3 show the load deflection plots and Figure 4 shows the P21 2010 calculations.

RISK AND LIMITATION OF LIABILITY: Scion's liability to the Client arising out of all claims for any loss or damage resulting from this work will not exceed in aggregate an amount equal to two times the Service Fees actually paid by the Client to Scion. Scion will not be liable in any event for loss of profits or any indirect, consequential or special loss or damage suffered or incurred by the Client as a result of any act or omission of Scion under this Agreement.

USE OF NAME: The Client will not use Scion's name in association with the sale and/or marketing of any goods or services

CAUTION

The information contained in this facsimile is confidential and may be legally privileged. If the reader of this message is not the intended recipient, you are hereby notified that any use, dissemination, distribution or reproduction of this message is prohibited. If you have received this message in error, please notify us immediately and return the message to us by mail. Thank you.




Figure 1: Wall 260323




Figure 2: Wall 260324




Figure 3: Wall 260325

P21:2010 BRACING RACKING TEST RESULT EVALUATION								
Wall Construction								
9mm grooved Panelline/PLANKWALL V100 board one side , Concrete floor								
50x3.0dia galv clouts at 150mm centres, 300 centres to middle stud								
25x0.9mm + 30x2.5 clouts as 12kN straps + P21 restraints								
90x45 SG8 H1.2 framing 600mm c/c's								
Calculated to BRANZ P21:2010, AS/NZS1170.2&5, NZS3604:2010						Summary		
Scion, Private Bag 3020 Rotorua. Timber Engineering Lab						Earthquake 134 (U) BU/m		
Date of test:- 13-Oct-11						Wind 124 (S) BU/m		
Date of calc's:- 13-Oct-11						Tested by Doug Gaunt		
Ship No. 2592						Analysed by Doug Gaunt		
Job No. TE11-028								
Serviceability Cycles				Ultimate Cycles			Wall dimensions	
Lab Number	Direction	Cycle to H/300 or DLQ or		Cycle to Displacement		L(mm)	H(mm)	
		8.0	X mm	y=(mm)		1200	2400	
		Loads	Residual	Maximum		d at P/2	4th,R	
		(P ₈)	Defln, C	Load	def @ P	d mm	kN	
		kN	mm	P(kN)	y (mm)			
260323	+	4.60	2.70	9.10	40.0	4.55	7.4	
	-	4.55	2.70	9.32	40.0		7.95	
260324	+	3.92	3.50	9.30	40.0	4.65	9.6	
	-	4.70	2.00	10.10	40.0		8.50	
206325	+	4.20	2.00	8.90	40.0	4.45	9.0	
	-	4.45	2.50	8.65	40.0		7.75	
		(P ₈)	(C)	(P)	(y)	P/2 (kN)	(d)	(Ry)
Averages		4.40	2.57	9.23	40.00	4.55	8.67	8.06
Coefficient of Variation %		6.05	19.82	4.91	0.00	1.79	10.71	2.97
y = average failure deflection or peak deflection of the three tests.								
d= average first cycle displacement at half peak, (the very first cycle wall reaches the load)								
R = Residual load, P = Peak Load, S = Serviceability load								
Displacement Recovery Factor (K1), (0.8 <= K1 <= 1.0)						Systems factor K2 = 1.2		
Average Structural Displacement Ductility factor						u = y/d 4.62		
Ductility Modification factor						K4 = 1.00		
DLW = Selected deflection limit for wind forces				DLQ = Selected deflection limit for earthquake forces				
P21:2010 BR Calc's								
Lab Number	K1	EQ ultimate	EQ service	Wind Ultimate	Wind Service			
	(= 1.4 - C/X)	BU's	BU's	BU's	BU's			
260323	1.00	161.7	199.6	184.2	154.6			
260324	1.00	165.0	188.1	194.0	145.7			
206325	1.00	157.0	188.7	175.5	146.2			
<20% Result Check	260323	0% Ok result	6% Ok result	0% Ok result	6% Ok result			
	260324	3% Ok result	-3% Ok result	7% Ok result	-3% Ok result			
	206325	-4% Ok result	-3% Ok result	-8% Ok result	-3% Ok result			
Note: Where the value of BR Wind or BR EQ for any specimen is more than 20% greater than either of the other two specimens, assign it a value of 1.2 times the lower value before averaging.								
Average Earthquake BR		Ultimate			Serviceability			
EQ (BU's)	20 x K4 x Ry =	161	(P8 x K1) x (K2/0.55) =		192			
		134 BU/m	Limited by		Ultimate limit state			
Average Wind BR		Ultimate			Serviceability			
Wind (BU's)	20 * P =	185	(P8 x K1) x (K2/0.71) =		149			
		124 BU/m	Limited by		Serviceability limit state			

Figure 4: P21 calculations for 1200mmx2.4m 9mm Panelline/PLANKWALL V100 walls on a concrete floor.

Please feel free to contact me to discuss this information as necessary.

Doug Gaunt 