80MM ROUND · FS-80

80MM DOWNPIPE



FS-80

Our most specified round downpipe. FS-80 is the default pairing for the residential spouting range. This product is a roll-formed lock seamed downpipe.

Ideally suited for most residential roofs, and the standard pairing for our spouting range.

- 80mm round roll-formed downpipe
- 5,020mm² cross-section capacity
- Strap or clamp bracket options
- Brackets at up to 2400mm centres
- Colour matched to your spouting
- Up to 20 year material warranty

SPECIFY YOUR 80MM DOWNPIPE

FINISH RANGE	DOWNPIPE MATERIAL	COLOUR CHOICE	BRACKETS
CG Range	ColorCote MagnaFlow pre-painted G300 steel, min 200gsm	17 CG Colours	Strap or clamp
Designer Range	ColorCote MagnaFlow pre-painted G300 steel, min 200gsm or ColorSteel Maxam, min 150gsm	25 Designer Colours	Strap or clamp
Specialty Range	ColorCote MagnaFlow pre-painted G300 steel, min 200gsm or ColorSteel Maxam, min 150gsm	20 Specialty Colours	Strap or clamp
Copper	¾ hard pure copper, grade C12200	Natural patina	Strap or clamp

AVAILABLE FITTINGS

95° and 30° bends, spreader tees, spreader end caps, branch tees, joiners, drain covers

CAPACITY

5,020mm² cross-section

For downpipe calculations by roof area, refer to MRM Code of Practice sections 5.4.1, 5.4.2 and 5.7.



80mm Downpipe



80mm Downpipe Strap



80mm Adjustable clamp



80mm 95° bend



80mm 30° bend



80mm Tee Junction

0800 50 1993
www.continuous.co.nz
cg@continuous.co.nz

All information, images and drawings are correct at time of publication August 2026