

Simpson Strong-Tie Stainless Steel Trim Head screws are ideal fastners for many exterior timber applications, including weatherboards, window and door facings, boxed corners and even aluminium window and door jambs.

Features and Benefits

- No pre-drilling required.
- Consistent countersink means no punching required.
- Trim head for clean and less noticeable finish.
- Unique "box" thread design with raised-ridge technology greatly reduces driving torque.
- Easy to reverse out means no broken boards if you need to remove the fastener.
- BRANZ Appraised for performance you can trust.*
- Suitable for NZS 3604 extra high wind zones.

Installation



Scan the QR code or follow the link to watch a video of the Collated Trim Head Screw. http://bit.ly/F-F-SSDTH

Please Note: Install weatherboards as per the manufacturers specification.



BRANZ Appraisal No. 1044



Simpson Strong-Tie Collated Trim Head Screws have been appraised by BRANZ for use to affix timber weatherboards to timber framing.

Follow the link to find out more. http://bit.ly/1044-19

*Loose offering not included in current Branz Appraisal

Trim Head Exterior Timber Screws The efficient and faster way to install

Weatherboards, Facings and Boxed Corners

SIMPSON Strong-Tie

Collated for Quik Drive - Trim Head Exterior Timber Screws Corrosion Resistance Level Box Thread • 305 Stainless Steel · Sharp point • #2 Sq. drive HIGH Compatible Tool: PRO300 Bit(s) included with every box of screws

Dia. Length Model No. **Replacement Bit** Barcode Box Qty Dimensions (WxLxH) SSDTH212S 7 g 65 mm BIT2S-RC10 746056055167 1000 273 x 365 x 124 mm 4.36 kg 7 g 75 mm SSDTH3S BIT2S-RC10 746056057697 1000 273 x 365 x 124 mm 5.27 kg

Loose - Trim Head Exterior Timber Screws • 305 Stainless Steel

• Box Thread

Sharp point







T-20 6-lobe drive



Bit(s) included with every box of screws

Corrosion Resistance Level

HIGH

| Dia. | Length | Model No. | Replacement Bit | Barcode | Box Qty | Box/ Ctn | Dimensions | Box (WxLxH) |
|------|--------|-----------|-----------------|--------------|------------|-------------|----------------|---------------|
| | | | | | | | | Ctn (WxLxH) |
| 9 a | 64 mm | S08250WPP | BIT20T-2-R2 | 744039616077 | 350 | 6 – | 102 x 152 x 15 | 2 mm 1.53 kg |
| 8 g | | | | | | | 203 x 465 x 16 | 0 mm 9.19 kg |
| 8 g | 76 mm | S08300WPP | BIT20T-2-R2 | 744039616107 | 350 | 6 – | 102 x 152 x 15 | 2 mm 1.93 kg |
| | | | | | | | 203 x 465 x 16 | 0 mm 11.59 kg |
| 0 | 89 mm | S09350WP1 | BIT20T-2-R2 | 707392336372 | 70 | 10 - | 102 x 76 x 76 | 6 mm 0.48 kg |
| 9 g | | | | | | | 104 x 396 x 16 | 0 mm 4.81 kg |

Simpson Strong-Tie® (New Zealand) Ltd Call 09 477 4440 www.strongtie.co.nz

Simpson Strong-Tie Limited Warranty: For the Limited Warranty that applies to Simpson Strong-Tie products, please consult www.strongtie.co.nz/warranty. To obtain a copy of the Limited Warranty, contact us at info.nz@strongtie.com, or at the number provided here. The Limited Warranty contains important disclaimers, limitations and exclusions, and applies only if the products have been properly specified, installed, maintained, and used in accordance with the design limits and the structural, technical, and environmental specifications in the Simpson Strong-Tie Documentation. All future purchases of Simpson Strong-Tie products are subject to the terms of the Limited Warranty in effect as of the purchase date.