

# CBSDG — Cement Sheet/Underlay/Timber-to-Steel (Collated)

**Material**

Carbon Steel

**Finish**

Class 3 Mechanically Galvanised



**Size:** See the table below

**Features & Benefits**

- Drill Point with wings drives easily through 1.2mm–2.4mm steel without pre-drilling
- Ribbed Flat Head with Nibs for countersunk finish
- Winged design avoids sheet ride
- #2 undersized square drive

**Applications**


- Cement Sheet/Underlay/Timber-to-Steel
- Steel Frame
- Recommended steel thickness; 0.8mm–2.4mm CBSDG Series, 1.2mm–3mm CBSDGL Series



**Ribbed Flat Head with Nibs** for easy countersinking



**Wings to cut clearance hole** means no sheet ride



**Drill Point design** easily drills into 0.8mm–3mm steel without the need for pre-drilling



**Quik Drive**<sup>®</sup>

**Specifications - Quik Drive<sup>®</sup> Collated**

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
CBSDG1SA	8G x 25mm	Fine Threads 18 TPI	Drill Point	Carbon Steel Class 3 Mechanically Galvanised	2500	#2 Undersize Square Drive	BIT2SU-RC10
CBSDG114SA	8G x 32mm						
CBSDG158SA	8G x 42mm						
CBSDGL158SA	10G x 42mm						
CBSDGL214SA	10G x 55mm						
CBSDGL3SA	10G x 75mm						

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.