

Page 1 of 2

NOVATHERM WARM ROOF SYSTEM

Self-adhesive waterproof roofing membrane, vapour barrier and thermal insulation

January 2025

PURPOSE AND SCOPE OF USE:

The NOVATHERM Warm Roof System is a thermally insulated roof & deck waterproofing system consisting of the NOVA-SK self adhered, two-layer membrane system applied over thermal insulation board and a vapour barrier. A warm roof system guarantees a continuous and efficient thermal resistance (R-value), negating condensation build up and creating energy savings.

The system is designed for use on exposed flat roofs and decks, with UV and weather resistance suitable for any location and wind zone in New Zealand. NOVA-SK is our only two-layer waterproofing membrane system to have a completely flameless installation making it a highly sought-after solution where a torch-on membrane is not desired.

Suitable for new builds and refurbishments, residential and commercial construction.

NOVATHERM Warm Roofs can be overlaid with Fixplus or other approved pedestals, pavers and decking, Kraitec Step walkway tiles, or SOPRASOLAR non-penetrative solar panel supports or other approved supports. Suitable for other waterproofing applications with written approval by Equus Industries Ltd.

PRODUCTS:

The system encompasses a selection of the products below. Refer to standard specifications for full specification details. Technical datasheets and specifications can be found on www.equus.nz.

EQUUS Peel and Stick Primer	Mechanical Fixings
SOPRASTICK	Eurothane Silver PIR Board
COLPHENE 3000	SOPRA-ISO PIR Board
NOVA-SK	SOPRAROCK HD 60 Mineral Wool
NOVA-SK MINERAL	Permabase Dek
DUO EASY FOAM	Liquid Membrane Detailing
COLTACK EVOLUTION 750	

SPECIFICATIONS:

NOVATHERM on concrete substrate	
NOVATHERM on plywood substrate	
NOVATHERM on metal substrate	
Masterspec 4421EN Equus NOVA-SK Roof & Deck Membrane by SOPREMA	

COLOUR:

Standard Cap Sheet Colours: Dark Grey

CONDITIONS OF USE:

In areas of regular foot traffic, higher than for normal maintenance traffic, the membrane must be overlaid with Fixplus pedestals and pavers or decking, Kraitec Step walkway tiles or other approved protection.

The product must be installed by a Certified Equus Applicator. Verification of their status can be confirmed by a current applicator certificate or by contacting Equus Industries. Any installation must be done in accordance with the latest specifications and technical documentation, or with written approval by Equus Industries Ltd.






4421EN Equus Nova-SK Flameless Roof & Deck Membrane by Soprema

Equus Industries Ltd. 4 Sheffield St, Blenheim 7274 | Phone: 03 578 0214 | Email: info@equus.nz | Web: www.equus.nz

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.





Page 2 of 2

NOVATHERM WARM ROOF SYSTEM

Self-adhesive waterproof roofing membrane, vapour barrier and thermal insulation

January 2025

BUILDING CODE COMPLIANCE:

B2 Durability - B2.3.1 (b), NOVATHERM Warm Roof has a durability of at least 15 years, when installed with the correct specification, installation and maintenance. See CodeMark CMNZ70151, BRANZ Appraisal 1169, BRANZ Appraisal 520.

E2 External moisture - E2.3.1, E2.3.2, E2.3.7 Test data, together with in-service history in New Zealand and internationally, of the correctly installed NOVATHERM Warm Roof over correctly designed and constructed substrates, show that the membrane successfully resists the ingress of moisture. See CodeMark CMNZ70151, BRANZ Appraisal 1169, BRANZ Appraisal 520.

E3 Internal moisture - E.3.3.1 NOVATHERM Warm Roofs provide the habitable buildings with adequate thermal resistance and R-values that are equal to or above those specified in E3/AS1. See BRANZ Appraisal 1169.

F2 Hazardous building materials - F2.3.1 Well known experience with the type of materials used together with in-service history, show that NOVATHERM complies with this performance requirement. Refer to SDS at www.equus.nz

H1 Energy efficiency - H1.3.1 (a) NOVATHERM Warm Roofs provide the building with adequate thermal resistance and R-values that are equal to or above those specified in H1/AS1 and H1/AS2. See BRANZ Appraisal 1169

SUPPORTING DOCUMENTATION:

The following additional documentation supports the above statements:

Title (type)	Version	URL
Codemark Certificate CMNZ70151	30 June 2023	www.equus.nz/content/reports/codemark-soprema-waterproofing-membranes.pdf
BRANZ Appraisal No. 520	08 June 2023	www.equus.nz/content/reports/branz-appraisal-nova-sk-520.pdf
BRANZ Appraisal No. 1169	02 November 2022	www.equus.nz/content/reports/branz-appraisal-warmroof-1169.pdf
Technical Datasheets for products listed on page 1 of this document		Technical datasheets can be found on www.equus.nz.

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No

MANUFACTURER CONTACT DETAILS:

Manufacture location	New Zealand
Legal and trading name of manufacturer	Equus Industries Ltd.
Manufacturer address for service	4 Sheffield Street, Blenheim 7274
Manufacturer website	www.equus.nz
Manufacturer email	info@equus.nz
Manufacturer phone number	03 578 0214
Manufacturer NZBN	9429032000306