



Stain Proof



Fade Resistant



Environmentally Responsible



Antistatic



Suitable For Underfloor Heating



Suitable For Stairs



Anti-Allergenic



5 Year Needlepunch Warranty



GUT



cradle to cradle
SILVER

Construction	Needlepunch carpet
Yarn	100% Polypropylene
Width	4.0m
Standard Roll Length	40m
Total Weight	±498g/m ²
Total Thickness	6.1mm
Backing	None
Electrical Properties	Antistatic
Fire Rating	CRF 8.0kW/m ² (ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Use	Indoor
Rating	Commercial
Stair Rating	Suitable
Warranty	5 Year Needlepunch Warranty
Environmental	Low VOC. Meets all PRODIS-GUT requirements. Cradle to Cradle Certified Silver
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. It is recommended that the carpet be adhered directly to the subfloor, which should be clean, dry and level. All adjacent pieces must be laid running in the same direction. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.