## Fahrenheit

## Belgotex<sup>®</sup>

























$\angle$	$\supset$

Stain Resistant

Responsible

Underfloor Heating

Stairs

Construction	Tufted textured loop pile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m <sup>2</sup>
Yarn Weight	576g/m²
Total Weight	4550g/ m²
Pile Height	2.8mm
Total Thickness	5.8mm
Machine Gauge	1/10th
Primary Backing	Non-woven Polyester / Nylon
Secondary Backing	PVC
Electrical Properties	Antistatic
Electrical Propensity	0.2kV (ISO 6356)
Fire Rating	CRF 4.5kW/m² (ASTM E 648)
VOC Rating	<0.5mg/m²/h - Green Label Plus ASTM D5116-06
Anti-allergenic Properties Will not shed or pill. Resistant to mould & mildew.	
Acoustic Insulation	23dB (ISO 140-8)
Acoustic Absorption	αω 0.15 (EN ISO 11654)
Dimensional Stability	<0.20% (EN 986)
Castor Chair Resistance	R ≥2.4 (DIN 54324)
Thermal Insulation	0.04m²k/W (ISO 8302)
Underfloor Heating	Suitable
Colour Fastness	5/5 on Grey Scale (AATCC/16)
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Commercial Warranty
Environmental	Low VOC, solution dying uses no water ISO 14001, Green Label Plus Certification
Installation	Laying recommendation: Quarter turn or Brick.  Please contact Gilt Edge Industries for all adhesive and installation instructions.  NB: If recommended adhesive is not used, claims will not be accepted.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Must be laid in accordance with AS/NZ Installation Standards.