



Construction	Heterogeneous Sheet Vinyl	
Width	4.0m	
Standard Roll Length	±22m	
Pattern Repeat	<b>Design:</b> 3D Abstract Coral Reef Flatweave Herringbone Galaxy Grass Jungle Riverstone Treadplate Water Absolute Concrete Black Stud Checker Board Malthouse Brick Marble	<b>Pattern Repeat:</b> 4000mm x 4000mm 4000mm x 4000mm 500mm x 1000mm 4000mm x 4000mm 2000mm x 2000mm 2000mm x 2000mm 666mm x 1000mm 1000mm x 1000mm 1500mm x 4000mm 2000mm x 2000mm 500mm x 500mm 570mm x 570mm 4000mm x 6050mm 4000mm x 3200mm
Total Weight	2800g/m <sup>2</sup>	
Wearlayer Thickness	0.70mm	
Total Thickness	2.0mm	
Surface Protection	PU Lacquer	
Slip Resistance	R10 (DIN 51130)	
Electrical Propensity	<2kV (EN 1815)	
Fire Rating	CRF 9.2 kW/m <sup>2</sup> (EN ISO 9239-1)	
Acoustic Insulation	ΔLw 6dB (ISO 717/2)	
Dynamic Coefficient of Friction	>0.6 (EN 13893)	
Wear Group	T (EN 660-2)	
Dimensional Stability	≤0.40% (EN ISO 23999, EN 434)	
Curling	≤8mm (EN ISO 23999)	
Thermal Resistance	0.014m <sup>2</sup> K/w (ISO 8302)	
Thermal Insulation	0.14W/m/K (EN 12524)	
Residual Indentation	≤0.20mm (EN ISO 24343-1, EN 433)	
Indoor Air Quality	FloorScore®, A+ Emissions	
Chemical Resistance	Resistant (EN ISO 26987, EN 423)	
Light Fastness	≥6 (EN ISO 105B02)	
Underfloor Heating	Suitable	
Classifications	Class 34 Commercial Very Heavy / Class 43 Industrial Heavy	
Warranties	10 Year Commercial Warranty	
Environmental	100% Phthalate Free, 100% Recyclable ISO 14001, ISO 9001	
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.	

- For samples, range and warranty details please contact us on 0800 377 753 or [belgotex.co.nz](http://belgotex.co.nz)
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.