

Warranty & Maintenance

Project Name & Location _____

Signed _____ Name _____ Installation Date _____

Warranty

Tick your fence type

<input type="checkbox"/> DuraPanel™ Aluminium	5 years (not within 0.5km of ocean or 1.5m from salt water pool)
<input type="checkbox"/> DuraPanel™ Pre-galvinised	5 years (not within 1km of ocean or 1.5m from salt water pool)
<input type="checkbox"/> SentryPanel Aluminium	5 years (not within 0.5km of ocean or 1.5m from salt water pool)
<input type="checkbox"/> SentryPanel Pre-galvinised	5 years (not within 1km of ocean or 1.5m from salt water pool)
<input type="checkbox"/> ColourPanel	10 years (not within 1km of ocean or 1.5m from salt water pool)
<input type="checkbox"/> ColourSlat Steel	10 years (not within 1km of ocean or 1.5m from salt water pool)
<input type="checkbox"/> SmartWall	10 years on metal components (not within 1km of ocean or 1.5m from salt water pool) 50 years warranty on timber treatment & 40 years warranty on glue lamination
<input type="checkbox"/> SleekWall	10 years (not within 0.5km of ocean or 1.5m from salt water pool)
<input type="checkbox"/> Green Screen	3 years (not within 1km of ocean or 1.5m from salt water pool)
<input type="checkbox"/> PicketPanel	5 years (not within 0.5km of ocean or 1.5m from salt water pool)
<input type="checkbox"/> Gate Automation	1 year

All products must be installed according to Boundaryline instructions and recommended practise

Maintenance

- Avoid earth or soil coming in contact with the fence
- Automation of sliding gates track and rack must be clear of debris, (i.e., stones, leaves, sand, etc)
- Fertilisers and garden chemicals should not be used in or around fences to limit contact
- Slope all concrete away from post to limit any water build up around base of post
- All fences and gates should be cleaned on a regular basis with a soft brush and a mild detergent solution
- Do not use harsh abrasive products
- In a salt water pool application, the fencing should be washed down after each swim
- Materials should not be leaned on or stacked against the fence to avoid the fence being pushed out of alignment
- Where ball bearing hinges are installed, they should be oiled regularly
- Automation of swing gates drilling screws, rivet shanks and other steel particles must be removed immediately to avoid rust and staining
- Angle grinders should not be used to cut fencing
- Aluminium posts should not be set directly into rapid or quick setting concrete. Posts should be insulated to avoid direct contact with these products as the additive reacts with aluminium

Proof of purchase will be required prior to admission of any warranty claim. Warranty applies only if above maintenance procedures are adhered to. Ball bearing hinges and automated motors will fail if not oiled as recommended and warranty will be void. On inspection, any build up of salt voids warranty as this indicates lack of maintenance. Use of heavy cleaners, such as brick acid, will void warranty. Powder coat decorative finish will incur natural fading over time from UV; this is not covered by warranty.

