





**Extrusion: 92740 / 92740**  
**Description: Bi-fold Door Stiles**




Centres	Spans for each wind zone			
	Low	Medium	High	Very High
500	3520	3206	2848	2622
600	3319	3024	2688	2476
700	3159	2879	2562	2361
800	3029	2762	2459	2267
900	2920	2663	2373	2190

**Extrusion: 93140 / 93150**  
**Description: French Stiles**



Centres	Spans for each wind zone			
	Low	Medium	High	Very High
500	3415	3110	2763	2544
600	3220	2934	2609	2403
700	3066	2794	2486	2292
800	2939	2680	2387	2202
900	2834	2585	2304	2127

**Extrusion: 93720 / 93700**  
**Description: Two plus One Stiles**



Centres	Spans for each wind zone			
	Low	Medium	High	Very High
500	3378	3076	2734	2517
600	3185	2902	2581	2377
700	3033	2765	2460	2268
800	2908	2652	2362	2179
900	2804	2558	2280	2105

Spans are the maximum calculated allowable, based on NZS4211:2008, which requires that the member deflection at serviceability wind pressure (SWP) shall not exceed 1/200 of the span. Hardware and componentry may further restrict the spans.

For advice we recommend you contact APL Technical Advisory Service