



Made in NZ from high strength northern radiata pine. Laminated, H5 treated and planed to achieve a smooth clean visual post.

- Post applications include: verandas, carports and supporting decks and roofs
- Manufacturing to AS/NZS1328:1998, AS5068:2006
- Treated in accordance to NZS3640:2003
- Posts must be fully painted within 14 days of installation. All cuts, notches and holes must be treated with a timber preservative
- The portion of the post in-ground must be sealed prior to being cast in concrete
- 88x88, 112x112 and 135x135 sizes
- 1.5m up to 6.0m long

Dimensional stability and treated for in ground use.



Specification table

Post size (mm)	88x88, 112x112, 135x135
Post lengths (m)	1.5, 2.4, 2.4, 3.0, 3.6, 4.2, 4.8, 6.0
Laminate species	Radiata pine (GL8)
Surface finish	Planed, Visual
Edge profile	Edge arrised
Preservative treatment	CCA H5 (laminate treatment)
Bond Type	Structural "A" Bond
Third party certification	Grade Right (NZ)
Durability	Min 50 years to meet NZBC clause B2
Manufacturing standard	AS/NZS 1328:1998

For full product information






NZWOOD

NEW ZEALAND WOOD PRODUCTS LIMITED

9 149 Kerrs Rd, Wiri, Auckland



Tech Info Line: 0800-022-352

Phone: +64-9-268 6540





