

VERTICAL SLIDING WINDOWS

MAIN FEATURES

- For residential and commercial use
- A counter-balanced, double hung system where both panels move together
- A good option for non-projecting ventilation
- In fully open position with both sashes adjoining each other half the window area is open
- Double hung windows will generally be appropriate in single banks because of the large width of coupling bars
- Shugg window available where moving panes of glass substitute for aluminium sashes.

FRAME TYPES

Contemporary Frame with flat, clean face in keeping with Metro Series aesthetics.

SASH TYPES

Beaded sash for single and double glazing

FLASHINGS

FIRST has a range of standard flashings.

FINISH / COLOUR

Powder Coated in a wide range of colours.

Anodised silver or bronze as standard, 12 micron thickness. Other colours and thicknesses are available.

GLASS

Double glazed units to a maximum of 30mm thickness are possible. Minimum single glazed glass thickness is 4mm. Other glass thicknesses may be used in accordance with NZS 4223: Glazing in Buildings. The full range of glass types can be included in this product. For further information consult your local FIRST manufacturer.

PERFORMANCE

FIRST complies with NZS4211: 2008 Performance of Windows. Certificates provided on request.

A guarantee for all FIRST products is provided under normal conditions of use against failure of materials and workmanship for five years from the date of practical completion.

SIZES

Weight restriction per panel of 50kg. Recommended aspect ratio of 2:1.

HARDWARE

An upward opening lever handle is fitted to the bottom rail of the lower sash.