

Latitude



Door frame and Latitude bottom rail (thermally broken option).




Latitude tongue and groove joints.



Standard Latitude door stile.

Key Features

- Aluminium clad doors combining tongue and groove boards (100mm wide) within a border of strong rails and stiles
- Glass inserts (20mm double glazing only) are available with a flat-faced contemporary moulding as standard
- Boards can be vertically or horizontally aligned
- Maximum door size supplied 2150mm high x 960mm wide
- Matching pairs of doors
- Doors are filled with high density foam for thermal efficiency and sound dampening
- Thermally broken stiles and rails can be included as an option - also allowing dual colour doors
- A wide range of door handle and lock options is available. Multi-point locking can be included and is recommended
- Dense, rigid construction means Latitude doors rate highly for impact resistance.



Contemporary flat-faced glazing bead is used.



Urbo, Icon and Elemental lever handles.

Specifications

Dimensions

Height 2150mm x 960mm wide. Onsite trimming possible where required

Maximum Glass Thickness

18mm double glazing as standard

Thermal Values

Consult APL Technical Department

Performance

Consult APL Technical Department

Design Considerations

- Installation in sheltered environments recommended - away from full sun exposure
- Inward opening entrance doors are generally favoured
- Multiple locking points and robust aluminium construction
- Double opening doors (French style) or opening sidelights possible for full-width access.
- The Virtual Home entrance door tool allows you to explore the style, colour and hardware options and give clients an indication of what their preferences look like. Visit the Altherm, First or Vantage website.