



Classic door frame and section.

### Key Features


- Aluminium clad doors with the capability to display a range of rectangular patterns and glazed inserts
- Applied mouldings can be either scrolled or flat-faced, the latter offering a more contemporary look
- Glass beads take the form of the two moulding designs on offer
- Arched-top glazed inserts are possible
- Doors are filled with high density foam for thermal efficiency and sound dampening
- Thermally broken stiles and rails can be included as an option – also allowing dual colour doors
- Double doors are possible with rebated meeting stiles
- Matching sidelights are available which can be either fixed or opening, for full-width access
- A wide range of door handle and lock options are available.




Classic door stile (non-thermal option).



Classic door moulding/ bead options.



Double door meeting stiles (non-thermal option).



Classic panel with opening sidelight (right).

### Specifications

#### Dimensions

The standard Classic door panel size is 1980mm high x 810mm wide. A non-standard panel to a maximum size of 2150mm high x 960mm wide is also available

#### Maximum Glass Thickness

18mm double glazing as standard

#### Thermal Values

Consult APL Technical Department

#### Performance

Consult APL Technical Department

### Design Considerations

- Installation in sheltered environments recommended – away from full sun exposure
- Inward opening entrance doors are generally favoured
- Multiple locking points and robust aluminium construction
- Double opening doors (French style) or opening sidelights possible for full-width access.
- The Virtual Home entrance door tool allows you to explore the style, colour and hardware options and give clients an indication of what their preferences look like. Visit the Altherm, First or Vantage website.