

HALE 3mm WALL PANELLING



Hale 3mm Wall Panelling is a 3mm thick Compact Laminate incorporating the same properties and benefits of 13mm Compact laminate.

Being 3mm, the panels are light weight and installed easily using a silicone modified adhesive directly onto a smooth, clean, dry substrate such as Gib board or Ply– no reduction to internal spaces through the use of battens.

Available in two sizes; 2440 x1220 and 3660 x 1525mm (Indent) with associated jointers, capping and corners in silver anodised aluminium.

Significantly the Hale Compact Laminates offer a Fire Certification that achieves 1-s to the New Zealand Building code Clause 3.

This allows the panels to be used in a fire egress situation.

Offering an Anti-Microbial, Anti-Fungal, Anti-Graffiti, High Impact and water resistance, the 3mm is suitable for the following areas;

- Toilet Blocks
- Gyms
- Changing rooms
- Laundries
- Showers
- Commercial Kitchens
- Health Care
- Rest Homes
- Prisons



Features and Benefits;

• Space Saving	• High Impact resistance
• Light Weight	• Anti-Microbial
• Easy Installation	• Anti-Fungal
• Cost Effective	• Colours available on Request
• Hygienic	• Water Resistant
• Easy Clean	
• Fire Resistant	

3mm Wall Panel System Overview:

- Installation on to flat smooth surface
- Suitable substrate – Gib board, Ply,
- Aluminium jointers, corners and caps available
- Water Resistant
- Suitable for Wet Area lining
- Suitable for Fire Egress
- Impact Resistant
- Range of colours
- Anti-Microbial
-

Edge Treatment:

- Compact Laminate
 - ≈ None (oil will enhance black edge)
 - ≈ Aluminium Caps and Jointers

Warranties:

- 3mm Compact Laminate board – 7 years

Features:	3mm Compact board
1-S Fire Rating	✓
Impact resistant	✓
Moisture resistant	✓
Panel Sizing – 2440 x 1220, 3660 x 1525mm	✓
Wet Area Lining - Showers	✓
Fire Egress	✓
Aluminium jointers and corners available	✓
Environmentally friendly, low emissions	✓

Uses :	
Bathroom Areas	✓
Shower Walls	✓
Fire Egress	✓
Splashbacks	✓

Updated August 2017

