

# Frame Kit (S) Installation Instructions




Retractable Insect Pleated Screen



Read Installation Instructions carefully before proceeding  
Ensure that Installation Instructions remain with Householder




## Recommended Tools






NOTE: SHARP ALUMINUM BLADE ONLY

## "S" Kit Components




or




**NOTE: ALL DIMENSIONS mm [inches]**

## Frame Preparation




$X = \text{RSTS} = 40 [1.57]$  or  
 $\text{RSTTS} = 60 [2.36]$

Measure internal opening width (**W**)



**SINGLE SCREEN**

$\text{RSTS or RSTTS} = W - (\text{PW} - 20 [0.78])$   
 $\text{RSCS} = W - (\text{PW} - 20 [0.78])$






**DOUBLE SCREEN**


$\text{RSTS or RSTTS} = W - (\text{PW} \times 2) - 40 [1.57]$   
 $\text{RSCS} = W - (\text{PW} \times 2) - 40 [1.57]$

**NOTE: PW = Panel Width**


## Cutting & Fitting RSTS, RSTTS, RSCS




$X = \text{RSTS} = 40 [1.57]$  or  
 $\text{RSTTS} = 60 [2.36]$





**NOTE: RSCS, RSTS OR RSTTS IS SUPPLIED PRE-DRILLED**





## Cutting & Fitting RSJ

Measure internal opening height (H).



Sliding Panel must come in contact with the seal

