

The 995C has a high purity die cast zinc alloy case to provide rigidity and precision. Major internal components are made of either stainless steel or sintered steel/ copper alloy to provide durability and strength.

The final product has been rigorously tested in accelerated wear tests and testimony to the quality of the 995MF Series is shown through the extensive use in the Australian and New Zealand markets.







Features

- Designed to suit hollow stile metal door sections with internal depths from 39mm and narrow stile timber and french doors
- The multi-function case allows easy conversion of a vestibule lock function (inside handle free) to a combination lock function (both handles locked) by a simple external operation
- The reversible stainless steel latch adjusts for inwards/outwards opening and left/right hand without case disassembly
- The latch is deadlatched by a stainless steel subbolt that retracts automatically with the main latch
- The 995MF case will accept bolt-through fixing for 159mm vertical fixing door furniture such as the Legge 5300/5400 Series narrow stile furniture
- Follower will accept 7.6mm-8mm furniture spindles, with no adjustment necessary
- A threaded pin is used for secure cylinder retention
- Designed to be compatible with most electric strikes

	Warranties	
Mechanical	30 years	
Finish	allegion.co.nz/finisheswarranty	



Specification guide

Function	Sub-function	Faceplate	Finish	Backset
Combination lockL9	Entry lock	Metal fix (short)blank Wood fix (long)W	Antique BronzeABZ Chrome PlateCP Oil Rubbed BronzePB Polished BrassPB Satin Black ChromeSBC Satin BrassSB Satin Brass UnlacqueredSBU Satin Chrome PlateSCP	23mmstandard 30mm30 38mm38

1.	Function Select the desired function e.g. Combination lockL9C
2.	Sub-function Select the required sub-function e.g. C1 Entry lock
3.	Faceplate Select the desired faceplate e.g. Wood fix
4.	Finish Select the desired finish e.g. Satin chrome plate
5.	Backset Select the desired backset e.g. 30mm

Finishes



Testing and Compliance



Security:Rated S8 and SL8 for physical security, SC7-SC8 for cylinder security and K6 for keying security



Corrosion:

Rated C7 for corrosion





Durability:

Rated D8 for durability



Legge 995C Combination Lock







- Key or turn locks or unlocks both handles simultaneously
- Automatic deadlocking by closing door
- Reversible bolt and function


Specifications

Door type	Timber or metal
Door thickness	Timber doors - 32mm to 48mm standard. Extended cylinders, spindles and strike plates available Metal doors - 35mm to 48mm standard. Designed to be used on hollow stile door sections, with a minimum internal depth of 39mm
Lock case	High purity zinc alloy
Outer forend	Satin stainless steel or brass
Bolt	Stainless steel
Sub-bolt	Stainless steel
Spindles	2 split spindles 32mm
Strike plate	Satin stainless steel or brass
Backsets	23mm standard. 30mm and 38mm available
Key cylinder	CC4 6 Pin keyway standard, Schlage C6 pin keyway optional, Schlage SR1 Restricted keyway optional, Schlage Everest Open & Restricted keyways optional





Forend & strike for wooden doors



Legge 995C Combination Lock

Sub-function Cams and adaptors C1 (RH) C2 (LH) - Entry lock **6A** Outside: Key retracts bolt at all times Inside: Turn locks and unlocks both handles C7 (RH) C8 (LH) - Double cylinder door lock 2 Outside: Key retracts bolt at all times Inside: Key locks and unlocks both handles C21 (RH) C22 (LH) - Entry lock **6A** Outside: Key locks and unlocks both handles Inside: Turn locks and unlocks both handles C23 (RH) C24 (LH) - Turn entry lock **1A** Outside: Key locks and unlocks both handles Inside: Turn operates bolt at all times

C27 (RH) C28 (LH) - Double cylinder door lock

Outside: Key locks and unlocks both handles Inside: Key locks and unlocks both handles




Legge 995C Accessories

Long lipped strike


Strikes for non-standard wooden jambs. Available in 50mm, 60mm, 70mm, 80mm & 90mm (A) **Finishes** Satin chrome plate, for

Finishes Satin chrome plate, for special finishes available refer to page 2



Short lipped strike

Strikes for non-standard jambs **Finishes** Satin chrome plate, for special finishes available refer to page 2





Legge 995C Combination Lock

Sub-function Cams and adaptors C31 (RH) C32 (LH) - Single cylinder door lock Outside: Key locks and unlocks both handles Inside: Handle operative except when locked by outside key C33 (RH) C34 (LH) - Privacy latch **6A** Outside: Emergency button unlocks both handles Inside: Turn locks and unlocks both handles C41 (RH) C42 (LH) - Exterior privacy latch **6A** Outside: Handle operative except when locked by inside turn Inside: Turn locks and unlocks both handles C49 (RH) C50 (LH) - Exterior lock 2 Outside: Handle operative except when locked by inside key Inside: Key locks and unlocks both handles C57 (RH) C58 (LH) - Passage latch Outside: Always operative Inside: Always operative



Legge 995C Cams and cam adaptors

1 1A (with adaptor) 2 5 6A (with adaptor)











