



## Claymark Ltd

Phone: 07 350 1085

Web: [www.claymark.co.nz](http://www.claymark.co.nz)

Email: [bruce.barclay@claymark.co.nz](mailto:bruce.barclay@claymark.co.nz)

## PRODUCT TECHNICAL STATEMENT (PTS)

### A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution

#### Description

The A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution is a cavity-based external wall cladding solution for residential and light commercial type buildings where domestic construction techniques are used.

The solution consists of horizontal concealed fixed A-lign® bevelback timber weatherboards, A-lign® profiled timber cavity battens, flashings and accessories and is finished with two coats of 100% premium acrylic house paint.

The solution incorporates a primary and secondary means of weather resistance (first and second line of defence) against water penetration by separating the cladding from the external wall frame with a nominal 20 mm drained cavity.

#### Scope

The A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution has been appraised as an external horizontally fixed wall cladding solution for buildings within the following scope:

- the scope limitations of NZBC Acceptable Solution E2/AS1, Paragraph 1.1; and,
- constructed with timber framing complying with the NZBC; and,
- with a risk score of 0-20, calculated in accordance with NZBC Acceptable Solution E2/AS1, Table 2; and,
- situated in NZS 3604 Wind Zones up to, and including Extra High.

The A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution has also been appraised as an external horizontally fixed wall cladding solution for specifically designed buildings within the following scope:

- the scope limitations of NZBC Acceptable Solution E2/AS1, Paragraph 1.1; and,

- constructed with timber framing complying with the NZBC; and,
- situated in specific design wind pressures up to a maximum design differential ultimate limit state (ULS) of 2.5 kPa.

The A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution is appraised for use with aluminium window and door joinery that is installed with vertical jambs and horizontal heads and sills. *(BRANZ Appraisal No. 751 (2011) A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution relies on the joinery meeting the requirements of NZS 4211 for the relevant Wind Zone or wind pressure.)*

## Building Regulations

### New Zealand Building Code (NZBC)

The A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution, if designed, used, installed and maintained in accordance with the statements and conditions of BRANZ Appraisal No. 751, will meet the following provisions of the NZBC:

**Clause B1 STRUCTURE:** Performance B1.3.1, B1.3.2 and B1.3.4. The A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution meets the requirement for loads arising from self-weight, wind, impact and creep [i.e. B1.3.3 (a), (h), (j) and (q)].

**Clause B2 DURABILITY:** Performance B2.3.1(b), 15 years, B2.3.1(c) 5 years and B2.3.2. The A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution meets these requirements.

**Clause E2 EXTERNAL MOISTURE:** Performance E2.3.2. The A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution meets this requirement.

**Clause F2 HAZARDOUS BUILDING MATERIALS:** Performance F2.3.1. The A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution meets this requirement and will not present a health hazard to people.

### Other Conditions or Limitations

No special conditions or limitations. Refer to BRANZ Appraisal No. 929 (2017) for general requirements.

### Technical Literature

A-lign® Cladding Concealed Fix Bevelback Weatherboard - Technical Manual, Version V.5 05/12, including CAD drawings 6.01 to 6.13 and 6.17 to 6.41.

### Consenting Applications

Do not base consent applications on a Product Technical Statement (PTS). Always refer to the supporting verification documentation, BRANZ Appraisal No. 751 A-lign® Bevelback Weatherboard Concealed Fix Cavity Solution.