

Juralco Stecca® Balustrade System

BPIR Declaration Version 07-26 v1

Designated building product Class 2

Declaration

Juralco Aluminium Building Products Ltd trading as Juralco has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Juralco Stecca® Balustrade System
------	-----------------------------------

Line

Identifier

Description

The Juralco Stecca® Postless Balustrading System is an architecturally based balustrade system that uses vertical slats in a standard and heavy-duty form, which removes the need for larger posts, enabling a continuous integrated panel design. Available as Face Fix and Top Fix.

Scope of use

Stecca® Balustrade

- Domestic and Residential Occupancy types A, A Other, B, C3 and E only
- Occupancy Types as per AS/NZ 1170.1.2002
- Balustrade options up to and including Extra High Wind Zone
- Complies With AS/NZS 1170:2002, NZS 4223.3.2016
- NZ Building Code B1, B2, F2, F4 and F9

Conditions of use

- The Juralco Stecca® Balustrade System manual details all extrusions and components used for the fabrication and installation/fixing of the system
- A Producer Statement 1(Design) is available. Copies of the above documents are available from: Juralco Aluminium Building Products Ltd, 48 Bruce McLaren Rd, Henderson, Auckland. Phone 09 478 8018 Fax 09 478 7883, Email specify@juralco.co.nz
- Any deviation from the standard fabrication or installation/fixing must be accompanied by a site-specific PS1 with site-specific calculations and drawings
- Only extrusions, components, and hardware supplied by or specified by JABP may be used in the Juralco Stecca® System
- Aluminium extrusions, components, and hardware – unless specified are manufactured to 6060 T5 specifications
- Stainless Steel components, hardware, fixings – all components to 316 grade
- The Juralco Stecca® Balustrade System must only be installed in accordance with the Juralco Stecca® Balustrade System manual
- Any deviation from that specified in the Juralco Stecca® manual must only be in accordance with this site-specific PS1, with site-specific calculations and drawings listing the non-standard details
- The Juralco Stecca® Balustrade System must only be fabricated/installed by a Juralco approved fabricator
- Upon completion of the installation, the fabricator must supply the owner with a PS3 (Construction)

Relevant building code clauses

B1	Structure	B1.3.1, B1.3.2, B1.3.3 (c, f, h, j, m), B1.3.4
B2	Durability	B2.3.1 (a), B2.3.2 (a, b)
F2	Hazardous building materials	F2.3.1, F2.3.3
F4	Safety from falling	F4.3.1
F9	Means of restricting access to residential pools	F9.3.1, F9.3.3

Contributions to compliance

NZBC Compliance

- The Juralco Stecca® Balustrade System has been reviewed by Lautrec Technology Group Ltd to demonstrate compliance with the structural requirements of the New Zealand Building Code and AS/NZS 1170: 2002 occupancy A, A Other, B, C3, and E, NZS 3604 Low, Medium, High, Very High, and Extra High Wind Zones
- The Structural Engineering design includes the requirements of B1 Structure, B2 Durability, F2 Hazardous material and F4 Safety from falling, all from the Building Code
- Verification Method B1 / VM1, B2/AS1, F4 / AS1, F9/AS1
- Complies with NZS 4223.3.2016

Supporting documentation

The following additional documentation supports the above statements:

BA Stecca Balustrade	07-26v1	www.eboss.co.nz/assets/literature/97/49043/BA-Stecca-Face-Fix-Balustrade-10-24-v1.pdf
Producer Statement Request	07-26v1	https://ps1.juralco.co.nz/
Juralco Warranty	24 September 2026	www.juralco.co.nz/assets/Product-Care-Warranty/Juralco-Warranty-Sheet-2026.pdf

For further information supporting Juralco Stecca® Balustrade System claims refer to our website.

Juralco Stecca® Balustrade System



BPIR Declaration

Contact details

Manufacture location	New Zealand
Legal and trading name of manufacturer	Juralco Aluminium Building Products Ltd trading as Juralco
Manufacturer address for service	48 Bruce McLaren Rd, Henderson, Auckland 0612
Manufacturer website	www.juralco.co.nz
Manufacturer email	specify@juralco.co.nz
Manufacturer phone number	0508 880 088
Manufacturer NZBN	9429037383664

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

I can also confirm that the Juralco Stecca® Balustrade System is not subject to a warning or ban under s26 of the Building Act.

Signed for and on behalf of **Juralco Aluminium Building Products Ltd trading as Juralco:**

Grant Boyce

Grant Boyce

Director

September 2026

JURALCO ALUMINIUM BUILDING PRODUCTS LTD TRADING AS JURALCO

48 Bruce McLaren, Henderson, Auckland, 0612, New Zealand

09 478 8018

www.juralco.co.nz

Appendix

BPIR Ready selections

Category: Balustrades systems

	Yes	No
Use as pool fencing	X	
Provides an accessible handrail	X	
Use of glass or other brittle material		X

Building code performance clauses

B1 Structure

B1.3.1

Buildings, building elements and sitework shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction or alteration* and throughout their lives.

B1.3.2

Buildings, building elements and sitework shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction or alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings, building elements and sitework*, including:

- (c) temperature
- (f) earthquake
- (h) wind
- (j) impact
- (m) differential movement

B1.3.4

Due allowances shall be made for:

- a. the consequences of failure,
- b. the intended use of the building,
- c. effects of uncertainties resulting from construction activities, or the sequence in which construction activities occur,
- d. variation in the properties of materials and the characteristics of the site, and
- e. accuracy limitations inherent in the methods used to predict the stability of buildings.

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- the life of the building, being not less than 50 years, if: those building elements (including floors, walls, and fixings) provide structural stability to the building, or those building elements are difficult to access or replace, or failure of those building elements to comply with the building code would go undetected during both normal use and maintenance of the building

B2.3.2

Individual *building elements* which are components of a *building system* and are difficult to access or replace must either:

- all have the same durability
- be installed in a manner that permits the replacement of building elements of lesser durability without removing building elements that have greater durability and are not specifically designed for removal and replacement

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation, or solid particles emitted by materials used in the *construction of buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

F2.3.3

Glass or other brittle materials with which people are likely to come into contact shall:

- a. if broken on impact, break in a way which is unlikely to cause injury or
- b. resist a reasonably foreseeable impact without breaking, or
- c. be protected from impact.

F4 Safety from falling

F4.3.1

Where people could fall 1 metre or more from an opening in the external envelope or floor of a *building*, or from a sudden change of level within or associated with a *building*, a barrier shall be provided.

F9 Means of restricting access to residential pools

F9.3.1

Residential pools must have or be provided with physical barriers that restrict access to the pool or the *immediate pool* area by unsupervised young children (i.e., under 5 years of age).

F9.3.3

A barrier surrounding a *pool* must have no permanent objects or projections on the outside that could assist children in negotiating the barrier. Any gates must

- a. open away from the pool; and
- b. not be able to be readily opened by children; and
- c. automatically return to the closed position after use.